



SALES CONTACT :



e-mail : support@njt.co.id
 Website : <http://njt.co.id/>
 Facebook : <https://www.facebook.com/NJTonline>
 Twitter : <https://twitter.com/onlineNJT>
 Youtube : bit.ly/NJTonline-channel

5 Cara Order Mudah!

01	DIRECT LINE 021-6231 7156 & 021-6298 621
02	WHATSAAPP 0855 1200 306 & 0855 1200 267
03	PIN BB 04A65BFA & B458C6A9
04	WEB www.njtcfb.co.id
05	EMAIL tele.sales@njt.co.id



Services Center
 Pangaran Jayakarta : 021- 6018218
 Harco Mangga Dua : 021- 6124541

800-140-1216

Services Online Checking :
<http://www.njt.co.id>

Effective Date : 03 Januari 2022

FULL/MIDDLE TOWER CHASSIS												
Product	Part No.	Color Style	Stock	MSRP	Exterior Material	Interior Material	Dimension	Form Factor Type	I/O Panel	Side Windows	Note	Product Description
Stryker SE	SGC-5000W-KWN2	White	NA	Rp 2.450.000	Steel, plastic, mesh	Steel, plastic, mesh	578.5 x 250.0 x 605.6 mm	Micro-ATX, ATX, XL-ATX	USB 3.0 x2 USB 2.0 x2 Audio In & Out x1	Yes		Rear Expansion Slots 9+1, Fan Cooling Mounts Front: 120mm x2, Top: 200mm x1, or 140mm x2, or 120mm x2, Rear: 140mm x1, or 120mm x1 Bottom: 120mm x2, included Cooling Devices Front: 120mm White LED fan x2, 1200 RPM, 17 dBA, Top: 200mm Black fan x1, 1000 RPM, 23 dBA Rear: 140mm Black fan x1, 1200 RPM, 19 dBA, Power Supply Bottom Mount, Standard ATX PS2 / EPS 12V, Max CPU Cooler Height 186 mm / 7.3 In, Max GPU/PCI Card Length 322 mm / 12.7 In, Special Features Carrying Handle
MasterFrame Series												
MasterFrame 700	MCF-MF700-KGNN-S00	Black	L	Rp 2.801.000	Steel, Tempered Glass	Steel	702 x 306 x 410mm	SSI EEB, SSI CEB, XL-ATX, E-ATX, ATX, Micro ATX, Mini ITX	2x USB 3.1 Gen 2 Type-A, 1x USB 3.2 Gen 2 Type-C, 1x 3.5mm Headset Jack (Audio+Mic)	NA		EXPANSION SLOTS 8 5.25" DRIVE BAYS N/A 2.5" / 3.5" DRIVE BAYS (COMBO) Up to 4 (PSU cover) FAN SUPPORT - RIGHT SIDE 3x 120mm / 2x 140mm FAN SUPPORT - LEFT SIDE 3x 120mm / 2x 140mm RADIATOR SUPPORT - TOP Up to 360/420mm RADIATOR SUPPORT - RIGHT SIDE Up to 280/360mm RADIATOR SUPPORT - LEFT SIDE Up to 280/360mm CLEARANCE - CPU COOLER 158mm / 6.22inch CLEARANCE - PSU 210mm / 8.26inch CLEARANCE - GFX Up to 450mm / 17.71inch, 310mm / 12.20inch recommended for maximum compatibility
HAF Series												
HAF 500	H500-KGNN-S00	BLACK, WHITE	L	Rp 1.665.000	STEEL, MESH, PLASTIC	TEMPERED GLASS, STEEL	516 X 224 X 510MM	TX, MICRO ATX, ATX, SSI CEB, E-ATX*, (*UP TO 12" X 14.1", MAY IMPACT CABLE MANAGEMENT AND CASE FEATURES, REMOVE CABLE COVER AND GPU FAN BRACKET FEATURES)	2X USB 3.2 GEN 1 (FORMERLY USB 3.0), 1X USB 3.2 GEN 2 TYPE-C, 1X SINGLE AUDIO JACK, 1X RESET/ARGB BUTTON	Yes Tempered Glass		ARGB CONTROLLER ARGB HUB PRE-INSTALLED FANS - FRONT 2X 200MM ARGB FAN PRE-INSTALLED FANS - REAR 1X 120MM SICKLEFLOW PWM ARGB PRE-INSTALLED FANS - OTHERS 1X 120MM SICKLEFLOW PWM (GPU FAN) FAN SUPPORT - TOP 3X 120MM, 2X 140MM, 2X 200MM FAN SUPPORT - FRONT 3X 120MM, 2X 140MM, 2X 200MM, *200MM MOUNTING HOLE SPACING 154 x 154 W/ UP TO 30MM THICKNESS FAN SUPPORT - REAR 1X 120MM
MasterCase Series												
MasterCase H500P ARGB	MCM-H500P-MGNN-S01	Gun Metal / Black	R	Rp 2.230.000	Steel, Plastic, Tempered Glass	SECC	544 x 242 x 542mm	Mini ITX, Micro ATX, ATX, E-ATX*, (*support for up to 12" x 10.7", will limit cable management features)	2x USB 3.2 Gen 1 (formerly USB 3.0), 2x USB 2.0, 1x 3.5mm Audio Jack, 1x 3.5mm Mic Jack, 1x ARGB Controller, 1x ARGB 2-to-3 splitter	Yes Tempered Glass		PRE-INSTALLED FANS - FRONT 2x 200mm ARGB Fan PRE-INSTALLED FANS - REAR 1x 140mm, 1200RPM FAN SUPPORT - TOP 3x 120/140mm, 2x 200mm FAN SUPPORT - FRONT 3x 120/140mm, 2x 200mm FAN SUPPORT - REAR 1x 120/140mm RADIATOR SUPPORT - TOP 120mm, 140mm, 240mm, 280mm, 360mm RADIATOR SUPPORT - FRONT 120mm, 140mm, 240mm, 280mm, 360mm RADIATOR SUPPORT - REAR 120mm, 140mm CLEARANCE - CPU COOLER 190mm CLEARANCE - PSU 220mm CLEARANCE - GFX 412mm DUST FILTERS Top, Front, Bottom POWER SUPPLY SUPPORT Bottom mount, ATX
MasterCase H500P Mesh ARGB	MCM-H500P-MGNN-S11	Gun Metal Grey	R	Rp 2.230.000	Steel, Plastic, Tempered Glass, Mesh	SECC	544 x 242 x 542mm	Mini ITX, Micro ATX, ATX, E-ATX*, (*support for up to 12" x 10.7", will limit cable management features)	2x USB 3.2 Gen 1 (formerly USB 3.0), 2x USB 2.0, 1x 3.5mm Audio Jack, 1x 3.5mm Mic Jack, 1x ARGB Controller, 1x ARGB 2-to-3 splitter	Yes Tempered Glass		PRE-INSTALLED FANS - FRONT 2x 200mm ARGB Fan PRE-INSTALLED FANS - REAR 1x 140mm, 1200RPM FAN SUPPORT - TOP 3x 120/140mm, 2x 200mm FAN SUPPORT - FRONT 3x 120/140mm, 2x 200mm FAN SUPPORT - REAR 1x 120/140mm RADIATOR SUPPORT - TOP 120mm, 140mm, 240mm, 280mm, 360mm RADIATOR SUPPORT - FRONT 120mm, 140mm, 240mm, 280mm, 360mm RADIATOR SUPPORT - REAR 120mm, 140mm CLEARANCE - CPU COOLER 190mm CLEARANCE - PSU 220mm CLEARANCE - GFX 412mm DUST FILTERS Top, Front, Bottom POWER SUPPLY SUPPORT Bottom mount, ATX
MasterCase H500 ARGB	MCM-H500-IGNN-S01	Iron Grey	R	Rp 1.625.000	Steel, Plastic, Mesh	SECC	525 x 228 x 502mm	Mini ITX, Micro ATX, ATX, SSI CEB, E-ATX*, (*support for up to 12" x 10.7", will limit cable management features)	2x USB 3.2 Gen 1 (formerly USB 3.0), 2x USB 2.0, 1x 3.5mm Audio Jack, 1x 3.5mm Mic Jack, 1x ARGB Controller, 1x ARGB 2-to-3 splitter	Yes Tempered Glass		PRE-INSTALLED FANS - FRONT 2x 200mm ARGB Fan PRE-INSTALLED FANS - REAR 1x 120mm (Black) FAN SUPPORT - TOP 2x 120mm, 2x 140mm, 1x 200mm FAN SUPPORT - FRONT 3x 120mm, 2x 140mm, 2x 200mm FAN SUPPORT - REAR 1x 120mm RADIATOR SUPPORT - TOP 120mm, 140mm, 240mm RADIATOR SUPPORT - FRONT 120mm, 140mm, 240mm, 280mm, 360mm RADIATOR SUPPORT - REAR 120mm CLEARANCE - CPU COOLER 167mm/6.5" CLEARANCE - PSU 180mm/7.1" CLEARANCE - GFX 410mm/16.1" DUST FILTERS Top, Front, Bottom POWER SUPPLY SUPPORT Bottom mount, ATX
MasterCase H500P Mesh White ARGB	MCM-H500P-WGNN-S01	Gun Metal Grey	L	Rp 2.285.000	Steel, Plastic, Tempered Glass, Mesh	SECC	544 x 242 x 542mm	Mini ITX, Micro ATX, ATX, E-ATX*, (*support for up to 12" x 10.7", will limit cable management features)	2x USB 3.2 Gen 1 (formerly USB 3.0), 2x USB 2.0, 1x 3.5mm Audio Jack, 1x 3.5mm Mic Jack, 1x ARGB Controller, 1x ARGB 2-to-3 splitter	Yes Tempered Glass		PRE-INSTALLED FANS - FRONT 2x 200mm ARGB Fan PRE-INSTALLED FANS - REAR 1x 140mm, 1200RPM FAN SUPPORT - TOP 3x 120/140mm, 2x 200mm FAN SUPPORT - FRONT 3x 120/140mm, 2x 200mm FAN SUPPORT - REAR 1x 120/140mm RADIATOR SUPPORT - TOP 120mm, 140mm, 240mm, 280mm, 360mm RADIATOR SUPPORT - FRONT 120mm, 140mm, 240mm, 280mm, 360mm RADIATOR SUPPORT - REAR 140mm, 120mm CLEARANCE - CPU COOLER 190mm CLEARANCE - PSU 220mm CLEARANCE - GFX 412mm/16.2" DUST FILTERS Top, Front, Bottom POWER SUPPLY SUPPORT Bottom mount, ATX

MasterCase SL600M	MCM-SL600M-SGNN-500	Silver, Black	NA	Rp	3.310.000	Body Steel Front Panel Aluminum Top Panel Aluminum Left Side Panel Tempered Glass Right Side Panel Steel	SECC	544(L) x 242(W) x 573(H)mm	Mini-ITX, Micro-ATX, ATX (E-ATX* support up to 12" x 10.7", will limit cable management features)	Power-LED Color White HDD-LED Color White USB-Ports USB 3.1 Type C x 1, USB 3.0 Type A x 2, USB 2.0 Type A x 2 Audio In / Out 1x 3.5mm Headset Jack (audio+mic) & 1x 3.5mm Mic Jack Reset Switch N/A	Yes Tempered Glass	ROTATABLE PCI BRACKET WINDOW VERSATILE STORAGE BRACKET ADVANCED I/O PANEL ADJUSTABLE TOP VENTILATION Fan Control 4 step slide, 4pin PWM x 4 Pre-installed Fan(s) Top N/A Front N/A, Rear N/A Bottom 200mm PWM Fan x 2 (Speed: 400~800RPM / Connector: 4Pin) Fan Support Top 120mm x 3 or 140mm/200mm x 2 Front N/A, Rear N/A Bottom 120mm x 3 or 140mm/200mm x 2 Radiator Support Top 120mm, 140mm, 240mm, 280mm, 360mm (maximum thickness clearance-43mm) Front N/A, Rear N/A Bottom 120mm, 140mm, 240mm, 280mm, 360mm (maximum thickness clearance 72mm when the GFX is installed in the vertical position) Clearance CPU Cooler 193mm PSU 200mm, GFX 318mm, Dust Filters Bottom
MasterCase H500M	MCM-H500M-IHNN-500	IRON GREY	C	Rp	2.930.000	Steel, Plastic,	SECC	526 x 228 x 502mm	ATX, Micro-ATX, Mini-ITX	Power-LED Color: White HDD-LED Color: White USB-Ports: 2x USB 2.0, 2x USB 3.0 Audio In / Out: Yes	Yes Tempered Glass	Expansion Slots 7, 5.25" Drive Bays No, Combo 3.5" / 2.5" Drive Bays 2 2.5" SSD Drive Bays 2, RGB Control Onboard button on the RGB Controller or via the Reset Switch (1x 1-to-3 RGB Splitter Cable Included) Pre-installed Fan(s) - Top N/A, Pre-installed Fan(s) - Front 2x 200mm RGB Fan, Pre-installed Fan(s) - Rear 1x 120mm (Black) Fan Pre-installed Fan(s) - Bottom N/A, Fan Support - Top 2x 120mm / 1x 200mm, Fan Support - Front 3x 120mm / 2x 140mm / 2x 200mm Fan Support - Rear 1x 120mm, Fan Support - Bottom N/A Radiator Support - Top 120 / 140 / 240mm, Radiator Support - Front 120 / 140 / 200 / 240 / 280 / 360mm, Radiator Support - Rear 120mm Radiator Support - Bottom N/A, Clearance - CPU Cooler 167mm / 6.5" Clearance - PSU 180mm / 7.1", Clearance - GFX 410mm / 16.1" Cable Routing - Behind Motherboard Tray 30mm, Dust Filters Top, Front, Bottom, Power Supply Support Bottom Mount, ATX
MasterCase MC500Mt	MCM-M500T-RH5N-500	Metallic red-black	NA	Rp	3.192.000	Steel, Plastic,	SECC	544 x 242 x 574mm	E-ATX (up to 12" x 10.7"), ATX, Micro-ATX, Mini-ITX	USB 3.0 x 2, USB 2.0 x 2, Audio in / out	Yes Tempered Glass	Dimensions (LxWxH) 512 x 235 x 548mm; Motherboard Support E-ATX (up to 12" x 10.7"), ATX, Micro-ATX, Mini-ITX Expansion Slots 7, Drive Bays 5.25" 2; Combo 2.5" / 3.5" 4; SSD 2 Drive Bays Support 5.25" 2; Combo 2.5" / 3.5" 8 or 10 (with ODD bay removed); SSD 4 I/O Port USB 3.0 x 2, USB 2.0 x 2, Audio In / out (supports HD Audio); Pre-installed Fan(s) Front 140mm x 2 (1200RPM), Rear 140mm x 1 (1200RPM); Fan Support Front 120 / 140mm x 3; Rear 120 / 140mm x 1; Top 120 / 140mm x 2 Radiator Support Front 120 / 140 / 240 / 280 / 360mm; Rear 120 / 140mm Top 120 / 140 / 240 / 280mm Clearance VGA 412mm (without 3.5" HDD cage); 295mm (with 3.5" HDD cage) CPU 190mm; Cable Routing Behind MB Tray 25mm - 35mm Dust Filters Top, Front, Bottom; Power Supply Support Bottom mount, ATX Extra Features Extra solid front panel
HAF Series												
HAF 500 White	H500-WGNN-500	White	L	Rp	1.665.000	Steel, Mesh, Plastic	SECC	516 x 224 x 510mm	Mini-ITX, Micro-ATX, ATX, SSI CEB, E-ATX* (*supports up to 12" x 12.2" motherboards, may impact cable management features)	USB Ports 2 x USB 3.2 Gen 1 (USB 3.0) 1x USB 3.2 Gen 2 Type C Audio In / Out 1 x single Audio jack Other ARGB Hub	Yes Tempered Glass	Pre-installed Fan(s) Front 2 x 200mm ARGB Fans Rear 1 x 120mm SickleFlow ARGB Fan Top on HDD cage 1 x 120mm SickleFlow non-led Fan Fan Support Top 3 x 120mm / 2 x 140mm / 2 x 200mm Front 3 x 120mm / 2 x 140mm / 2 x 200mm *200mm Mounting Hole Spacing 154 x 154 w/ up to 30mm thickness Rear 1 x 120mm Top on HDD cage 1 x 120mm Radiator Support Top 120 / 140 / 240 / 280 / 360mm Front 120 / 140 / 200 / 240 / 280 / 360mm Rear 120mm Clearance CPU Cooler 167mm / 6.5" Power Supply 180mm / 7.1" GraphicsCard 410mm / 16.1"
MasterBox Series												
MasterBox 540	MB540-KGNN-500	Black	R	Rp	1.527.000	Steel, Mesh, Plastic, Tempered Glass		499.3 x 208.6 x 498mm	Mini ITX, Micro ATX, ATX, E-ATX*, ("up to 12" x 10.7" motherboards, may impact cable management feature)	2x USB 3.2 Gen 1 Type-A, 1x USB 3.2 Gen 2 Type-C, 1x 3.5mm Headset Jack (Audio+Mic), 1x Reset/ARGB button	Yes (Tempered Glass)	ARGB Ether Front Panel Standardized ARGB Connector & Controller Included Removable Top Panel Rich Connectivity Screwless & Tool-Free Design TG Side Panel Versatile Cooling Options Room For Upgrades Breathable Power Supply Shroud
MasterBox MB600L V2 w/ODD Steel	MB600L2-KN5N-500	Black	R	Rp	723.000	Steel, Plastic,		405.5x204x455.3mm	Mini ITX, Micro ATX, ATX	2x USB 3.2 Gen 1 Type-A, 1x 3.5mm Headset Jack (Audio+Mic)	N/A	ODD Support Brushed Front Panel Hexagon Gleam Mesh Intakes With ODD Support Versatile Cooling Options Breathable Power Supply Shroud Room For Upgrades Removable HDD Cage
MasterBox MB600L V2 wo/ODD	MB600L2-KGNN-500	Black	L	Rp	723.000	Steel, Plastic, Tempered Glass		405.5x204x455.3mm	Mini ITX, Micro ATX, ATX	2x USB 3.2 Gen 1 Type-A, 1x 3.5mm Headset Jack (Audio+Mic)	Yes Tempered Glass	No ODD Support Brushed Front Panel Hexagon Gleam Mesh Intakes With/Without ODD Support Versatile Cooling Options Breathable Power Supply Shroud Room For Upgrades Removable HDD Cage

MasterBox MB511 ARGB	MCB-B511D-KGNN-RGA	Black	R	Rp	1.102.000	Steel, Plastic, Tempered Glass	SECC	496 x 217 x 469 mm	Mini ITX, Micro ATX, ATX, SSI CEB, E-ATX*, (*support for up to 12" x 10.7", will limit cable management features)	2x USB 3.2 Gen 1 (formerly USB 3.0), 1x 3.5mm Audio Jack, 1x 3.5mm Mic Jack, 1x ARGB Controller, 1x ARGB 2-to-3 splitter	Yes Tempered Glass	PRE-INSTALLED FANS - FRONT 3x 120mm ARGB Fans FAN SUPPORT - TOP 3x 120mm, 2x 140mm FAN SUPPORT - FRONT 3x 120mm, 2x 140mm FAN SUPPORT - REAR 1x 120mm RADIATOR SUPPORT - TOP 120mm, 240mm, 360mm, (44mm max motherboard component height) RADIATOR SUPPORT - FRONT 120mm, 140mm, 240mm, 280mm, 360mm, (75mm clearance) RADIATOR SUPPORT - REAR 120mm CLEARANCE - CPU COOLER 165mm/6.49" CLEARANCE - PSU 180mm/7.08" CLEARANCE - GFX 410mm/16.1" DUST FILTERS Front, Top, Bottom POWER SUPPLY SUPPORT Bottom mount, ATX
MasterBox TD300 Mesh	TD300-KGNN-500	Black	R	Rp	1.156.000	Steel, Mesh, Plastic, Tempered Glass	SECC	433x 210x 420.5mm	Micro ATX, Mini ITX	Audio In / Out 1 x 3.5mm Audio Jack 1 x 3.5mm MicJack Other ARGB Hub	Yes Tempered Glass	Pre-installed Fan(s) Top N/A Front 2 x 120mm SickleFlow PWM ARGB fans Rear N/A Bottom N/A Fan Support Top 2 x 120mm / 2 x 140mm
MasterBox 500	MB500-KGNN-500	Black	R	Rp	1.153.000	Steel, Mesh, Plastic	SECC	516 x 224 x 510mm	Mini-ITX, Micro-ATX, ATX, E-ATX* (*up to 12" x 10.7" motherboards, may impact cable management feature)	USB Ports 2 x USB 3.2 Gen1 Type-A Audio In / Out 1x 3.5mm Headset Jack (Audio + Mic) Other 1x RESET/ARGB button	Yes Tempered Glass	Top N/A Front 1 x 120mm SickleFlow PWM ARGB Rear 1 x 120mm MF120 Fan Support Top 3 x 120mm / 2 x 140mm Front 3 x 120mm / 2 x 140mm Rear 1 x 120mm Radiator Support Top 120 / 140 / 240 / 280 / 360mm (recommended maximum thickness 55mm) Front 120 / 140 / 240 / 280 / 360mm Rear 120mm Clearances CPU Cooler 165mm / 6.49" Power Supply 180mm / 7.08" (295mm / 11.61" withHDD cage removed) GraphicsCard 410mm / 16.1"
MasterBox TD500 Mesh w/ctrl	MCB-D500DKGNN-S01	Black	L	Rp	1.308.000	Steel, Plastic, Tempered Glass, Mesh	SECC	493 x 217 x 469 mm	Mini ITX, Micro ATX, ATX, SSI CEB, E-ATX*, (*support for up to 12" x 10.7", will limit cable management features)	2x USB 3.2 Gen 1 (formerly USB 3.0), 1x 3.5mm Audio Jack, 1x 3.5mm Mic Jack, 1x ARGB Controller (only for the S01 versions), 1x ARGB 2-to-3 splitter	Yes Tempered Glass	PRE-INSTALLED FANS - TOP N/A PRE-INSTALLED FANS - FRONT 3x 120mm ARGB Fans PRE-INSTALLED FANS - REAR N/A FAN SUPPORT - TOP 3x 120mm, 2x 140mm FAN SUPPORT - FRONT 3x 120mm, 2x 140mm FAN SUPPORT - REAR 1x 120mm RADIATOR SUPPORT - TOP 120mm, 240mm, 360mm, (44mm max motherboard component height) RADIATOR SUPPORT - FRONT 120mm, 140mm, 240mm, 280mm, 360mm RADIATOR SUPPORT - REAR 120mm CLEARANCE - CPU COOLER 165mm/6.49" CLEARANCE - PSU 180mm/7.08", 295mm/11.61" (w/ HDD cage removed) CLEARANCE - GFX 410mm/16.1" CABLE ROUTING 19mm/0.74" DUST FILTERS Top, Front, Bottom POWER SUPPLY SUPPORT Bottom mount, ATX
MasterBox TD500 Mesh White	MCB-D500DWGNN-500	White	L	Rp	1.308.000	Steel, Plastic, Tempered Glass, Mesh	SECC	493 x 217 x 469 mm	Mini ITX, Micro ATX, ATX, SSI CEB, E-ATX*, (*support for up to 12" x 10.7", will limit cable management features)	2x USB 3.2 Gen 1 (formerly USB 3.0), 1x 3.5mm Audio Jack, 1x 3.5mm Mic Jack,	Yes Tempered Glass	PRE-INSTALLED FANS - TOP N/A PRE-INSTALLED FANS - FRONT 3x 120mm ARGB Fans PRE-INSTALLED FANS - REAR N/A FAN SUPPORT - TOP 3x 120mm, 2x 140mm FAN SUPPORT - FRONT 3x 120mm, 2x 140mm FAN SUPPORT - REAR 1x 120mm RADIATOR SUPPORT - TOP 120mm, 240mm, 360mm, (44mm max motherboard component height) RADIATOR SUPPORT - FRONT 120mm, 140mm, 240mm, 280mm, 360mm RADIATOR SUPPORT - REAR 120mm CLEARANCE - CPU COOLER 165mm/6.49" CLEARANCE - PSU 180mm/7.08", 295mm/11.61" (w/ HDD cage removed) CLEARANCE - GFX 410mm/16.1" CABLE ROUTING 19mm/0.74" DUST FILTERS Top, Front, Bottom POWER SUPPLY SUPPORT Bottom mount, ATX
MasterBox TD500 Crystal	MCB-D500D-KGNN-SAU	Black	NA	Rp	1.308.000	Steel, Plastic, Tempered Glass	SECC	493 x 217 x 469mm	Mini ITX, Micro ATX, ATX, SSI CEB, E-ATX*, (*support for up to 12" x 10.7", will limit cable management features)	2x USB 3.2 Gen 1 (formerly USB 3.0), 1x 3.5mm Audio Jack, 1x 3.5mm Mic Jack	Yes Tempered Glass	PRE-INSTALLED FANS - TOP N/A PRE-INSTALLED FANS - FRONT 3x 120mm ARGB Fans PRE-INSTALLED FANS - REAR N/A FAN SUPPORT - TOP 3x 120mm, 2x 140mm FAN SUPPORT - FRONT 3x 120mm, 2x 140mm FAN SUPPORT - REAR 1x 120mm RADIATOR SUPPORT - TOP 120mm, 240mm, 360mm, (44mm max motherboard component height) RADIATOR SUPPORT - FRONT 120mm, 140mm, 240mm, 280mm, 360mm RADIATOR SUPPORT - REAR 120mm CLEARANCE - CPU COOLER 165mm/6.49" CLEARANCE - PSU 180mm/7.08", 295mm/11.61" (w/ HDD cage removed) CLEARANCE - GFX 410mm/16.1" CABLE ROUTING 19mm/0.74" DUST FILTERS Top, Front, Bottom POWER SUPPLY SUPPORT Bottom mount, ATX
MasterBox K501L RGB	MCB-K501L-KGNN-SR1	Black	R	Rp	818.000	Steel, Plastic, Tempered Glass	SECC	499.5mm x 217mm x 468.5mm	ATX, Micro ATX, Mini ITX	1x USB 3.2 Gen 1 (formerly USB 3.0), 1x USB 2.0, 1x 3.5mm Audio Jack, 1x 3.5mm Mic Jack	Yes Tempered Glass	PRE-INSTALLED FANS - FRONT 1x 120mm (RGB) PRE-INSTALLED FANS - REAR 1x 120mm (Black) FAN SUPPORT - FRONT 2x 140mm, 3x 120mm FAN SUPPORT - TOP 2x 120/140mm FAN SUPPORT - REAR 1x 120mm RADIATOR SUPPORT - FRONT 120mm, 140mm, 240mm, 280mm, 360mm RADIATOR SUPPORT - TOP 120mm, 240mm RADIATOR SUPPORT - REAR 120mm CLEARANCE - CPU COOLER 165mm/6.49" CLEARANCE - PSU 390mm (without radiator and HDD installed), 200mm (with radiator and HDD installed) CLEARANCE - GFX 410mm (without radiator installed), 360mm (with radiator installed) CABLE ROUTING 19"=27mm DUST FILTERS Top, Front, Bottom POWER SUPPLY SUPPORT ATX PS2
MasterBox MB311L ARGB	MCB-B311L-KGNN-S02	Black	R	Rp	936.000	Steel, Mesh, Plastic, Tempered Glass	SECC	435.5 x 217.5 x 410mm	Micro ATX, Mini ITX	2x USB 3.2 Gen 1 (formerly USB 3.0), 1x 3.5mm Audio Jack, 1x 3.5mm Mic Jack	Yes Tempered Glass	PRE-INSTALLED FANS - FRONT 2x 120mm ARGB Fan FAN SUPPORT - TOP 2x 120/140mm FAN SUPPORT - FRONT 3x 120mm, 2x 140mm FAN SUPPORT - REAR 1x 120mm RADIATOR SUPPORT - TOP 120mm, 240mm RADIATOR SUPPORT - FRONT 120mm, 140mm, 240mm, 280mm RADIATOR SUPPORT - REAR 120mm CLEARANCE - CPU COOLER 166mm/6.54" CLEARANCE - PSU 140mm (HDD cage in backmost position), 325mm (w/o front radiator & HDD cage) CLEARANCE - GFX 344mm CABLE ROUTING 18-22mm DUST FILTERS Top, Front, Bottom POWER SUPPLY SUPPORT Bottom mount, ATX

MasterBox MB320L ARGB	MCB-B320L-KGNN-S02	Black	L	Rp	968.000	Steel, Mesh, Plastic, Tempered Glass	SECC	435.5 x 217.5 x 410mm	Micro ATX, Mini ITX	2x USB 3.2 Gen 1 (formerly USB 3.0), 1x 3.5mm Audio Jack, 1x 3.5mm Mic Jack	Yes Tempered Glass	PRE-INSTALLED FANS - FRONT 2x 120mm ARGB Fan FAN SUPPORT - TOP 2x 120/140mm FAN SUPPORT - FRONT 3x 120mm, 2x 140mm FAN SUPPORT - REAR 1x 120mm RADIATOR SUPPORT - TOP 120mm, 240mm RADIATOR SUPPORT - FRONT 120mm, 140mm, 240mm, 280mm RADIATOR SUPPORT - REAR 120mm CLEARANCE - CPU COOLER 166mm/6.54" CLEARANCE - PSU 140mm (HDD cage in backmost position), 325mm (w/o front radiator & HDD cage) CLEARANCE - GFX 344mm CABLE ROUTING 18-22mm DUST FILTERS Top, Bottom, Front POWER SUPPLY SUPPORT Bottom mount, ATX
MasterBox MB400L w/o ODD TG	MCB-B400L-KGNN-S00	Black	R	Rp	740.000	Steel, Plastic	SECC	411 x 218 x 410mm	Micro ATX, Mini ITX	2x USB 3.2 Gen 1 (formerly USB 3.0), 1x 3.5mm Headset Jack (Audio+Mic)	Yes Tempered Glass	PRE-INSTALLED FANS - TOP N/A PRE-INSTALLED FANS - FRONT N/A PRE-INSTALLED FANS - REAR 1x 120mm (Black) FAN SUPPORT - TOP 2x 120/140mm FAN SUPPORT - FRONT 3x 120mm, 2x 140mm FAN SUPPORT - REAR 1x 120mm RADIATOR SUPPORT - TOP 120mm, 240mm RADIATOR SUPPORT - FRONT 120mm, 140mm, 240mm, 280mm RADIATOR SUPPORT - REAR 120mm CLEARANCE - CPU COOLER TG: 166mm CLEARANCE - PSU 140mm (HDD cage in backmost position), 325mm (w/o front radiator & HDD cage) CLEARANCE - GFX 344mm CABLE ROUTING 18-22mm, DUST FILTERS Top, Front, Bottom POWER SUPPLY SUPPORT Bottom mount, ATX
MasterBox CM694 TG	MCB-CM694-KG5N-S00	Black	R	Rp	1.790.000	Steel, Plastic, Tempered Glass, Mesh		493 x 224 x 506 mm	Mini ITX, Micro ATX, ATX, E-ATX	2x USB 3.0 Type A, 1x USB 3.1 Type-C, 1x 3.5mm Headset Jack (Audio+Mic)	Yes Tempered Glass	Size : Mid Tower Available Color(s) : Black Materials : Steel, Plastic, Tempered Glass, Mesh Dimensions (LxWxH) Steel: 493mm x 220mm x 506mm (incl. Protrusions), Steel: 482mm x 220mm x 477mm (excl. Protrusions), TG: 483mm x 224mm x 506mm (incl. Protrusions), TG: 482mm x 224mm x 477mm (excl. Protrusions) Motherboard Support : Mini ITX, Micro ATX, ATX, E-ATX
MasterBox MB530P	MCB-B530P-KHNN-S01	Black	C	Rp	1.735.000	Plastic Mesh Bezel	Steel Body	489 x 229 x 469mm	ATX, Micro-ATX, Mini-ITX	USB 3.0 x 2, USB2.0 x2, Audio In / Out, ARGB control button	Yes Tempered Glass	MASTERBOX MBS30P, 3 Tempered Glass Panels Aggressive Intakes' Addressable RGB Fans with Lighting Control Support for a Total of 6 Fans and Water Cooling Graphics Card Support Up to 410mm Cable Cover and Routing Space
MasterBox Pro 5 RGB with Controller	MCY-B5P2-KWGN-02	Black	NA	Rp	1.527.000	Steel body, Plastic mesh bezel	SECC	223x 475x 500 mm	E-ATX, ATX, Micro-ATX, Mini-ITX	2x USB 3.0 1x Audio In & Out	Yes Tempered Glass	Expansion Slots 7, Air Cooling Compatibility Front: 3x 120mm or 2x 140mm, Rear: 2x 120mm, Water Cooling Compatibility Front: 240/280/360mm radiator Rear: 120mm radiator Included Fans Front: 3x 120mm RGB fan (Additional controller or compatible motherboard required for RGB functionality) Rear: 1x 120mm Dust Filters Front / Bottom Power Supply Type Bottom Mount Standard ATX PS2 / EPS 12V Maximum CPU Cooler Height 167mm Maximum GPU/PCI Card Length 410mm
MasterBox Q500L Sakura	Q500L-KANN-SJP	White	R	Rp	897.000	Steel, Plastic,	Steel Body	490 x 203 x 426mm	ATX, Micro-ATX, Mini-ITX	USB 3.0 x 2, Audio In / Out		Dimensions (LxWxH) 490 x 215 x 426mm ; Motherboard Support ATX, Micro-ATX, Mini-ITX Expansion Slots 7; Drive Bays 5.25" 1, 3.5" 2, 2.5" 2 I/O Port USB 3.0 x 2, Audio In / Out; Pre-installed Fan(s) Rear 120mm x 1 black fan Fan Support Front 120mm / 140mm x 2; Top 120mm x 2; Rear 120mm x 1 Radiator Support Front 120/140/240/280mm radiator Rear 120mm radiator (Need to install fan first); Clearances CPU Cooler 157mm PSU 220mm; GPU 399mm; Cable Routing Behind MB Tray 22mm Dust Filters Front, Top, Bottom; Power Supply Bottom mount, ATX
MasterBox Q500L	MCB-Q500L-KANN-S00	Black	NA	Rp	897.000	Steel, Plastic	Steel Body	386(L) x 230(W) x 381(H) mm	ATX, Micro ATX, Mini ITX	2x USB 3.0, 1x 3.5mm Audio Jack, 1x 3.5mm Mic Jack	Acrylic	Exterior Color : Black Materials - Body, Steel, Plastic Materials - Side Panel: Acrylic Dimensions (LxWxH) : 386(L) x 230(W) x 381(H) mm Motherboard Support : ATX, Micro ATX, Mini ITX
MasterBox MS600 Silver	MCB-MS600-SGNN-S00	Silver	C	Rp	899.000	Steel, Plastic	Steel Body	460 x 213 x 446 mm	ATX, Micro-ATX, Mini-ITX	USB 3.0 x 2, Audio in / out	Tempered Glass	Expansion Slots 7, 5.25" Drive Bays N/A, 3.5" HDD Drive Bays 2 (Max. 2), 2.5" SSD Drive Bays 2 (Max. 4), *supports Max. 6 with optional brackets not included, I/O Panel USB 3.0 x 2, Audio In / Out; Pre-installed Fan(s) - Rear 120mm x 1, Fan Support - Front 120mm x 2 / 140mm x 2, Fan Support - Top N/A, Fan Support - Rear 120mm x 1 Fan Support - Bottom N/A, Radiator Support - Front 120mm / 140mm / 240mm, Radiator Support - Rear 120mm Clearance - CPU Cooler 160mm Clearance - Graphics Card 400mm Clearance - Power Supply 180mm
MasterBox MB500	MCB-B500D-KGNN-S00	Black	NA	Rp	999.000	Steel, Plastic, Tempered Glass	Steel Body	494 x 211 x 475mm	ATX, Micro-ATX, Mini-ITX	USB 3.0 x 2, Audio In / Out	Yes (Tempered Glass)	RGB Fans Drive Bays 3.5" HDD 2 (Max. 2) 2.5" SSD 2 (Max. 4), Pre-installed Fan(s) Front 120mm x 2 RGB LED fan Rear 120mm x 1 RGB LED fan, Fan Support Front 120mm x 1 / 140mm x 2 Top 120mm x 2 Rear 120mm x 1, Radiator Support Front 120 / 140 / 240 / 280 / 360mm radiator (limited) up to 50mm thickness without fan Rear 120mm x 1
MasterBox NR600 w/ODD	MCB-NR600-KGNN-S00	Black	NA	Rp	1.156.000	Steel, Plastic	Steel Body	478 (L) x 209 (W) x 473 (H) mm	ATX, Micro ATX, Mini ITX	USB 3.0 x 2, Audio In / Out	Yes	
MasterBox NR400 w/ODD	MCB-NR400-KGNN-S00		NA	Rp	979.000	Steel, Plastic	Steel Body	387 x 230 x 378mm	Micro-ATX, Mini-ITX	USB 3.0 x 2, Audio In / Out	Yes	
MasterBox Q300L Retro	MCB-Q300L-WANN-SRE	White	NA	Rp	718.000	Steel, Plastic	Steel Body	387 x 230 x 378mm	Micro-ATX, Mini-ITX	USB 3.0 x 2, Audio In / Out	Yes	Drive Bays 3.5" HDD 1 2.5" SSD 2, Pre-installed Fan Rear 120mm x 1 Fan Support Front 120 / 140mm x 2 Top 120mm x 2 Rear 120mm x 1 Bottom 120mm x 1 Radiator Support Front 120mm x 1 / 240mm x 1 Rear 120mm x 1 Clearances CPU Cooler 157mm
CMP 510	CP510-KGNN-S03	Black	R	Rp	756.000	Steel, Plastic, Tempered Glass	Steel Body	445 x 204 x 463mm	Mini ITX, Micro ATX, ATX	1x USB 3.2 Gen 1 Type-A, 1x USB 2.0, 1x 3.5mm Headset Jack (Audio+Mic), 1x ARGB Controller	Yes	2.5" / 3.5" DRIVE BAYS (COMBO) 2 2.5" DRIVE BAYS 2 FAN SUPPORT - TOP 2x 120mm, 2x 140mm FAN SUPPORT - FRONT 3x 120mm, 2x 140mm FAN SUPPORT - REAR 1x 120mm RADIATOR SUPPORT - TOP 120 / 240mm (Memory bar height limit 35mm, First assemble the memory and then assemble the Radiator) RADIATOR SUPPORT - FRONT 120mm, 140mm, 240mm, 280mm RADIATOR SUPPORT - REAR 120mm CLEARANCE - CPU COOLER 161mm CLEARANCE - PSU 160mm

MasterBox Q300L	MCB-Q300L-KANN-S00	Black	R	Rp	652.000	Steel, Plastic	Steel Body	387 x 230 x 378mm	Micro-ATX, Mini-ITX	USB 3.0 x 2, Audio In / Out	Yes		Drive Bays 3.5" HDD 1 2.5" SSD 2, Pre-installed Fan Rear 120mm x 1 Fan Support Front 120 / 140mm x 2 Top 120mm x 2 Rear 120mm x 1 Bottom 120mm x 1 Radiator Support Front 120mm x 1 / 240mm x 1 Rear 120mm x 1 Clearances CPU Cooler 157mm
MasterBox Q300P w/RGB fans	MCB-Q300P-KANN-S02	Black	NA	Rp	1.156.000	Steel, Plastic	Steel Body	450 x 230 x 450mm	Micro-ATX, Mini-ITX	USB 3.0 x 2, Audio In / Out	Yes	RGB Fans	Drive Bays 3.5" HDD 1 2.5" SSD 2 Pre-installed Fan(s) Front 120mm RGB LEDx 2 Rear 120mm non-LED x 1 Fan Support Front 120 / 140mm x 2 Top 120mm x 2 Rear 120mm x 1 Bottom 120mm x 1 Radiator Support Front 120mm x 1 / 240mm x 1 Rear 120mm x 1 Clearances CPU Cooler 157mm
Cosmos Series													
Cooler Master Casing Cosmos C700P Black Edition	MCC-C700P-KG5N-S00	Black	NA	Rp	4.825.000	Aluminum, Steel, Plastic	Aluminum, Steel	639 x 306 x 651mm	Mini-ITX, Micro-ATX, ATX, E-ATX (Support 12" x 11")	USB 3.1 Gen 2 Type C x 1, USB 3.0 x 4, Fan Speed & RGB control buttons, Audio In / Out (supports HD Audio)	Tempered Glass, Steel		Expansion Slots 8, Drive Bays 5.25" 1, 2.5"/3.5" HDD 2 2.5" SSD 2, Drive Bays support 5.25" 2, 2.5"/3.5" HDD 8 or 9 (with ODD bay removed), 2.5" SSD 2, I/O Port USB 3.1 Gen 2 Type C x 1, USB 3.0 x 4, Fan Speed & RGB control buttons, Audio In / Out (supports HD Audio), Pre-installed Fans Front 140mm fan x 2, 1200RPM, Rear 140mm fan x 1, 1200RPM, Fan Support Top 120/140mm fan x 3, Bottom* 120/140mm fan x 2, Front 120/140mm fan x 3, Rear 120/140mm fan x 1, Liquid Cooling Support Top 120mm, 140mm, 240mm, 280mm, 360mm (requires removal of ODD cage), Bottom* 120mm, 140mm, 240mm, Front 120mm, 140mm 240mm, 280mm, 360mm, 420mm (requires removal of ODD cage), Rear 120mm, 140mm Clearances CPU Cooler 198mm, GPU 490mm (without 3.5" HDD cage) 320mm (with 3.5" HDD cage), Power Supply Support Bottom Mount, ATX PS2, Lighting Support RGB Control Board x 1 (Cycle, Static, M/B modes) to embedded lightings One RGB connection available
Cosmos C700M	MCC-C700M-MG5N-S00	Grey, Silver, Black	NA	Rp	6.760.000	Steel	Steel	650(L) x 306(W) x 651(H)mm	Mini ITX, Micro ATX, ATX, E-ATX	I/O PORT - USB PORTS / USB 3.1 TYPE-C 1 I/O PORT - USB PORTS / USB 3.0 TYPE-A 4 I/O PORT - AUDIO - 3.5MM HEADSET JACK (AUDIO+MIC) 1 I/O PORT - AUDIO - 3.5MM MIC JACK 1 I/O PORT - FANS/LIGHTING 1	Tempered Glass, Steel		RAISING THE BAR(S) Highly Versatile Layout Graphics Card Mounting with Riser Cable Addressable RGB Lighting Extensive Cable Cover System Aluminum Panels & Handles Versatile Liquid Cooling Support Rich Connectivity Curved Tempered Glass Side Panel

SILENCIO SERIES													
Product	Part No.	Color Style	Stock	MSRP	Exterior Material	Interior Material	Dimension	Form Factor Type	I/O Panel	Side Windows	Note	Product Description	
CHS Silencio S600 TG	MCS-S600-KG5N-S00	Black	NA	Rp	1.371.000	Steel, Plastic, Tempered Glass, Sound Dampening Material		478mm x 209mm x 470.5mm (incl. Protrusions), 466mm x 209mm x 460.5mm (excl. Protrusions)	Mini ITX, Micro ATX, ATX	2x USB 3.2 Gen 1 (formerly USB 3.0), 1x 3.5mm Headset Jack (Audio+Mic), 1x SD card reader			Available Color(s) : Black Materials : Steel, Plastic, Tempered Glass, Sound Dampening Material Dimensions (LxWxH) : 478mm x 209mm x 470.5mm (incl. Protrusions), 466mm x 209mm x 460.5mm (excl. Protrusions) Motherboard Support : Mini ITX, Micro ATX, ATX
CHS Silencio S400 TG	MCS-S400-KG5N-S00	Black	NA	Rp	1.282.000	Steel, Plastic, Tempered Glass, Sound Dampening Material		418mm x 210mm x 408mm (incl. Protrusions), 403.5mm x 210mm x 400mm (excl. Protrusions)	Mini ITX, Micro ATX	2x USB 3.2 Gen 1 (formerly USB 3.0), 1x 3.5mm Headset Jack (Audio+Mic), 1x SD card reader			Available Color(s) : Black Materials : Steel, Plastic, Tempered Glass, Sound Dampening Material Dimensions (LxWxH) : 418mm x 210mm x 408mm (incl. Protrusions), 403.5mm x 210mm x 400mm (excl. Protrusions) Motherboard Support : Mini ITX, Micro ATX

MINI-ITX CHASSIS													
Product	Part No.	Color Style	Stock	MSRP	Exterior Material	Interior Material	Dimension	Form Factor Type	I/O Panel	Side Windows	Note	Product Description	
MasterBox NR200P Sakura	MCB-NR200P-WGNN-S1P	White / Pink	R	Rp	1.553.000	Steel, Plastic, Tempered Glass, Mesh		376 x 185 x 292mm	Mini-ITX and Mini DTX	2x USB 3.2 Gen 1 Type-A, 1x 3.5mm Headset Jack (Audio+Mic)	Tempered Glass, Steel		Limited Size, Unlimited Options Unrestricted Cooling Potential Triple-slot GPU support and Included Vertical Riser Cable Easy, Tool-free access 360 Degree Accessibility Multiple motherboard support options Out-of-the-box Custom Cooling Support High quality materials
MasterBox NR200P	MCB-NR200P-KGNN-S00	Black	L	Rp	1.264.000	Steel, Plastic, Mesh, Tempered Glass		376 x 185 x 292mm	Mini-ITX and Mini DTX	2x USB 3.2 Gen 1 Type-A, 1x 3.5mm Headset Jack (Audio+Mic)	Tempered Glass, Steel		Limited Size, Unlimited Options Unrestricted Cooling Potential Triple-slot GPU support and Included Vertical Riser Cable Easy, Tool-free access 360 Degree Accessibility Multiple motherboard support options Out-of-the-box Custom Cooling Support High quality materials
NR200P White	MCB-NR200P-WGNN-S00	White	R	Rp	1.311.000	Steel, Plastic, Mesh, Tempered Glass		376 x 185 x 292mm	Mini-ITX and Mini DTX	2x USB 3.2 Gen 1 Type-A, 1x 3.5mm Headset Jack (Audio+Mic)	Tempered Glass, Steel		Limited Size, Unlimited Options Unrestricted Cooling Potential Triple-slot GPU support and Included Vertical Riser Cable Easy, Tool-free access 360 Degree Accessibility Multiple motherboard support options Out-of-the-box Custom Cooling Support High quality materials
NR200P Cyan	MCB-NR200P-ACNN-S00	Caribbean Blue	R	Rp	1.371.000	Steel, Plastic, Mesh, Tempered Glass	Steel	376 x 185 x 292mm	Mini-ITX and Mini DTX	2x USB 3.2 Gen 1 Type-A, 1x 3.5mm Headset Jack (Audio+Mic)	Tempered Glass, Steel		Limited Size, Unlimited Options Unrestricted Cooling Potential Triple-slot GPU support and Included Vertical Riser Cable Easy, Tool-free access 360 Degree Accessibility Multiple motherboard support options Out-of-the-box Custom Cooling Support High quality materials

NR200P Pink	NR200P-QCNN-500	Flamingo Pink	R	Rp	1.371.000	Steel, Plastic, Mesh, Tempered Glass	Steel	376 x 185 x 292mm	Mini-ITX and Mini DTX	2x USB 3.2 Gen 1 Type-A, 1x 3.5mm Headset Jack (Audio+Mic)	Tempered Glass, Steel	Limited Size, Unlimited Options Unrestricted Cooling Potential Triple-slot GPU support and Included Vertical Riser Cable Easy, Tool-free access 360 Degree Accessibility Multiple motherboard support options Out-of-the-box Custom Cooling Support High quality materials
NR200P Purple	MCB-NR200P-PCNN-500	Nightshade Purple	R	Rp	1.371.000	Steel, Plastic, Mesh, Tempered Glass	Steel	376 x 185 x 292mm	Mini-ITX and Mini DTX	2x USB 3.2 Gen 1 Type-A, 1x 3.5mm Headset Jack (Audio+Mic)	Tempered Glass, Steel	Limited Size, Unlimited Options Unrestricted Cooling Potential Triple-slot GPU support and Included Vertical Riser Cable Easy, Tool-free access 360 Degree Accessibility Multiple motherboard support options Out-of-the-box Custom Cooling Support High quality materials
NR200P Orange	MCB-NR200P-OCNN-500	Sunset Orange	R	Rp	1.371.000	Steel, Plastic, Mesh, Tempered Glass	Steel	376 x 185 x 292mm	Mini-ITX and Mini DTX	2x USB 3.2 Gen 1 Type-A, 1x 3.5mm Headset Jack (Audio+Mic)	Tempered Glass, Steel	Limited Size, Unlimited Options Unrestricted Cooling Potential Triple-slot GPU support and Included Vertical Riser Cable Easy, Tool-free access 360 Degree Accessibility Multiple motherboard support options Out-of-the-box Custom Cooling Support High quality materials
NR200	MCB-NR200-KNNN-500	Black	NA	Rp	899.000	Steel, Plastic, Mesh, Tempered Glass		376 x 185 x 292mm	Mini-ITX and Mini DTX	2x USB 3.2 Gen 1 Type-A, 1x 3.5mm Headset Jack (Audio+Mic)	Mesh Steel	Unrestricted Cooling Potential Triple-slot GPU support Easy, Tool-free access 360 Degree Accessibility Multiple motherboard support options Out-of-the-box Custom Cooling Support High quality materials
NR200 White	MCB-NR200-WNNN-500	White	NA	Rp	899.000	Steel, Plastic, Mesh, Tempered Glass		376 x 185 x 292mm	Mini-ITX and Mini DTX	2x USB 3.2 Gen 1 Type-A, 1x 3.5mm Headset Jack (Audio+Mic)	Mesh Steel	Unrestricted Cooling Potential Triple-slot GPU support Easy, Tool-free access 360 Degree Accessibility Multiple motherboard support options Out-of-the-box Custom Cooling Support High quality materials
MasterCase H100	MCM-H100-KANN-500	Black	R	Rp	828.000	Plastic, Steel Mesh	Steel Alloy	312 x 216 x 301 mm	Mini ITX	2x USB 3.2 Gen 1 (formerly USB 3.0), 1x 3.5mm Audio Jack, 1x 3.5mm Mic Jack, 1x RGB Controller	No	A LITTLE GAME-CHANGER, Compact Mini-ITX, Fine Mesh Ventilation 200mm RGB Fan, ATX Power Supply Compatible Built-in Handle
Elite 110A	RC-110A-KKN1	Midnight Black	C	Rp	612.000	polymer front mesh panel	Steel Alloy	260 x 208 x 280 mm	Mini ITX /Pico-ITX /Nano ITX.	USB 3.0 x2, Audio In & Out x1	No	Color : midnight black. Appearance : polymer front mesh panel. Case body : Steel alloy. Dimensions : 260 x 208 x 280 mm. M/B Type : Mini-ITX. I/O Panel : USB 3.0 x 2, Audio In & Out.
Elite 130	RC-130-KKN1	Midnight Black	C	Rp	528.000	polymer front mesh panel	Steel Alloy	240 x 207.4 x 398.5 mm	Mini ITX /Pico-ITX /Nano ITX.	USB 3.0 x2, USB 2.0 x2, Audio In & Out x1	No	Color : Midnight Black. Appearance : polymer front mesh panel. Case body : Steel alloy. Dimensions : 240 x 207.4 x 398.5 mm. M/B Type : Mini-ITX. I/O Panel : USB 3.0 x 2, USB 2.0 x 1, Audio In & Out.

Accessories Mastercase												
Cooler Master Accessories NR200 PSU Bracket Bk	MCA-NR200C-KPSU00	Black	R	Rp	259.000	ATX PSU Bracket for NR200P /NR200						
Cooler Master Accessories NR200 PSU Bracket Wh	MCA-NR200C-WPSU00	White	R	Rp	259.000	ATX PSU Bracket for NR200P /NR200						
MstrCase5/6/H500P TempGlassSidePanel	MCA-M500R-TGSP00-LGT		R	Rp	233.000	MasterAccessory Tempered Glass Side Panel (Light Grey Tinted) for MasterCase 5, 6, MC500, MC600 and H500P by Cooler Master						
Dual-Curved TemperedGlassSidePanel	MCA-C700R-TGSP00-DBT		L	Rp	1.185.000	Dual-Curved Tempered Glass Side Panel for COSMOS C700 Series						
Cosmos C700P Rear Panel	MCA-C700C-KRP000		L	Rp	175.000	Rear Panel for COSMOS C700 Series						
LED Partition Plate -RGB (MC 5/6)	MCA-C500R-CLPP00		L	Rp	114.000	Designed for our MasterCaseMC500 & MC600 series, this MasterAccessoryallows you to replace the case's partition plate with a RGB LED lit one.						
Tmprd Glass S Panel MasterCase 3	MCA-C3P1-KGW00		C	Rp	175.000	MasterCase Pro 3 Tempered Glass Side Panel gives you a clean look of your hardware. Included is a Lock Mechanism to protect your hardware. Tempered Glass Side Panel (Dark Tint) , 2 Key for Lock Mechanism, Micro Fiber Cleaning Cloth						
Temperedglass masterbox 5,pro 5, 5t	MCA-B501C-TGSP00-LGT		L	Rp	217.000	Materials : Steel : Tempered Glass, Dimensions (L x W x H) : 499 x 513 x 60mm / 19.6 x 20.1 x 2.4 inch, Available Color : Light Grey Tinted, Warranty : 2 years. Compatible with: MasterBox 5, MasterBox Pro 5, MasterBox 5T						
Tempered glass masterbox lite 5	MCA-B500C-TGSP00-LGT		L	Rp	157.000	Materials : Steel : Tempered Glass, Dimensions (L x W x H) 476 x 496 x 59mm, Available Color : Light Grey Tinted, Compatible With: MasterBox Lite 5 Series, MasterBox MB500, MasterBox MB600, MasterBox K500L						
Tempered glass masterbox lite 3.1	MCA-B300C-TGSP00-LGT		L	Rp	131.000	Materials : Steel : Tempered Glass, Dimensions (L x W x H) : 463 x 398 x 53mm / 18.2 x 15.7 x 2.1 inch, Available Color : Light Grey Tinted, Warranty : 2 years. Compatible with: MasterBox Lite 3.1						
LED parttn plt mstrcase pro 3 Blue	MCA-C300R-BLPP00		L	Rp	103.000							
LED parttn plt mstrcase pro 3 Red	MCA-C300R-RLPP00		L	Rp	103.000							
Universal LED strip RGB	MCA-U000R-CLS000		NA	Rp	196.000	Material : Acrylic, Aluminum, Magnet, Dimensions : 220 x 15 x 15mm, Input Voltage : DC 12V, Installation : Magnetic, Power Consumption 15 * 0.1W : 1.5W, Cable Length: 400mm, Warranty : 1 Year						
Riser Cable PCIe 4.0 200mm	MCA-U000C-KPCI40-200		R	Rp	760.000	COMPATIBILITY PCIe 4.0 and older CERTIFICATIONS BK210933AC ELECTRONIC COMPONENT MATERIALS PCBA, Tinned Copper Wire 30 AWG INSULATION MATERIALS PE, TPE OTHER MATERIALS ABS, Nickel, Gold, PP, Brass CONNECTORS PCI-E x16 Male to PCI x16 90° Female CABLE LENGTH 200mm CONTACT CURRENT RATING 1.1A per contact pin MAX VOLTAGE RATING 30V WORKING VOLTAGE / CURRENT DC 12V / 5A PCB / WIRE UL NUMBERS E189572 / E252840 OPERATING TEMPERATURE-20° to +100° Celsius						
Riser Cable PCIe 4.0 300mm	MCA-U000C-KPCI40-300		R	Rp	880.000	COMPATIBILITY PCIe 4.0 and older CERTIFICATIONS BK210933AC ELECTRONIC COMPONENT MATERIALS PCBA, Tinned Copper Wire 30 AWG INSULATION MATERIALS PE, TPE OTHER MATERIALS ABS, Nickel, Gold, PP, Brass CONNECTORS PCI-E x16 Male to PCI x16 90° Female CABLE LENGTH 300mm CONTACT CURRENT RATING 1.1A per contact pin MAX VOLTAGE RATING 30V WORKING VOLTAGE / CURRENT DC 12V / 5A PCB / WIRE UL NUMBERS E189572 / E252840 OPERATING TEMPERATURE-20° to +100° Celsius						
Riser Cable PCI-e 200mm V2	MCA-U000C-KPCI30-200		R	Rp	514.000	Black, COMPATIBILITYmPCI-E 3.0, CERTIFICATIONS, EMI, IPC4101D/21,MATERIALS, PCBA, Copper Wire, INSULATION MATERIALS, PE, TPE, OTHER MATERIALS, ABS, Stainless Steel, Nickel, Gold, Brass, CONNECTORS, PCI-E x16 Male to PCI x16 90° Female, CABLE LENGTH, 200mm, CONTACT CURRENT RATING, 1.1A per contact pin, OPERATING TEMPERATURE, -20° to +100° Celsius, WEIGHT,90g						
Riser Cable PCI-e 300mm V2	MCA-U000C-KPCI30-300		R	Rp	558.000	Black, COMPATIBILITYmPCI-E 3.0, CERTIFICATIONS, EMI, IPC4101D/21,MATERIALS, PCBA, Copper Wire, INSULATION MATERIALS, PE, TPE, OTHER MATERIALS, ABS, Stainless Steel, Nickel, Gold, Brass, CONNECTORS, PCI-E x16 Male to PCI x16 90° Female, CABLE LENGTH, 300mm, CONTACT CURRENT RATING, 1.1A per contact pin, OPERATING TEMPERATURE, -20° to +100° Celsius, WEIGHT,90g						
Vertical VGA Holder Kit Gen4	MCA-U000R-KFVK02		C	Rp	885.000	DIMENSIONS (L X W X H) GFX Holder kit: 184 x 142 x 121mm / 7.25 x 5.59 x 4.77 inch (closed), GFX Holder kit: 239 x 142 x 121mm/ 9.41 x 5.59 x 4.77 inch (fully open), Riser cable: 165mm (6.49in) SUPPORTED GRAPHICS CARDS Any length, up to 2.5 slots wide COMPATIBILITY PCIe 4.0 and older CERTIFICATIONS BK210933AC PCB / WIRE UL NUMBERS E189572 / E252840 ELECTRONIC COMPONENT MATERIALS PCBA, Tinned Copper Wire 30 AWG INSULATION MATERIALS PE, TPE OTHER MATERIALS ABS, PP, SGCC Steel, Nickel, Gold, Brass CONNECTORS PCI-E x16 Male to PCI x16 90° Female WORKING VOLTAGE / CURRENT DC 12V / 5A OPERATING TEMPERATURE-20° to +100° Celsius						
ARGB GPU Support Bracket	MCA-U000R-GSBTG-00		R	Rp	391.000	Black MATERIALS ABS Plastic, Tempered Glass DIMENSIONS (L X W X H) 58 x 58 x 177mm / 2.29 x 2.29 x 6.97inch (Incl. Protrusions) ARGB CABLE LENGTH 510mm/20.1inch						
ELV8 VGA Holder	MAZ-IMG8-N3ONA-R1		R	Rp	369.000	MATERIAL Steel, Plastic DIMENSIONS (L X W X H) 305 x 52 x 6 mm / 12 x 2.0 x 0.2 inch LED RGB RATED VOLTAGE 5V WARRANTY 2 years						
Vertical VGA Holder Kit V2	MCA-U000R-KFVK01		R	Rp	617.000	Black, DIMENSIONS (L X W X H), GFX Holder kit: 184 x 142 x 121mm / 7.25 x 5.59 x 4.77 inch (closed), Riser cable: 165mm (6.49in), SUPPORTED GRAPHICS CARDS Any length, up to 2.5 slots wide, RISER CABLE MODEL, Riser Cable PCIe 3.0 Ver.2, COMPATIBILITY, PCI-E 3.0						
3.5"HDD Bracket3-Bay,MasterCase 5	MCA-0005-K3HDO		NA	Rp	227.000	Material Metal, Color Black, Supported Drive Size 3.5", Supported Drive Bay Size 5.25", What's in the Box 3-Bay Hard Drive Cage x1						
24 Pin Adapter Capacitor GL	CMA-CEMB01XXBK1-GL		NA	Rp	240.000	42(L) x 57(W) x 27(H)mm Color Black Material ABS 94v-0 plastic						

POWER SUPPLY											
Product	Part No.	Stock	MSRP	Certification	Modularity	CPU 4+4 Pin	SATA Connector	PCI Express Connector	4-Pin Molex	Fan	Warranty
V1200 Platinum	RSC00-AFBAG1-EU	NA	Rp 2.999.000	80 Plus Platinum	Full Modular	2	12	12	9	135mm Fluid Dinamic Bearing	7 Years
Product	Part No.	Stock	MSRP	Certification	Modularity	CPU 4+4 Pin	SATA Connector	PCI Express Connector	4-Pin Molex	Fan	Warranty
PSU V850 Gold V2 White Ediiton	MPY-850V-AGBAG	R	Rp 2.186.000	80Plus Gold	Full Modular	2	12	6	4	135mm Fluid Dinamic Bearing	10 Years
PSU V850 Gold V2	MPY-850V-AFBAG	R	Rp 2.120.000	80Plus Gold	Full Modular	2	12	6	4	135mm Fluid Dinamic Bearing	10 Years
PSU V750 Gold V2 White Ediiton	MPY-750V-AGBAG	R	Rp 1.861.000	80Plus Gold	Full Modular	2	12	6	4	135mm Fluid Dinamic Bearing	10 Years
PSU V750 Gold V2	MPY-750V-AFBAG	R	Rp 1.861.000	80Plus Gold	Full Modular	2	12	6	4	135mm Fluid Dinamic Bearing	10 Years
PSU V650 Gold V2 White Ediiton	MPY-650V-AGBAG	R	Rp 1.646.000	80Plus Gold	Full Modular	2	8	4	4	135mm Fluid Dinamic Bearing	10 Years
PSU V650 Gold V2	MPY-650V-AFBAG	R	Rp 1.646.000	80Plus Gold	Full Modular	2	8	4	4	135mm Fluid Dinamic Bearing	10 Years
PSU G800 Gold	MPW-8001-ACAAG-EU	R	Rp 1.535.000	80Plus Gold	Non Modular	2	6	4	3	120mm Hydrodynamic fan bearing	5 Years
PSU G700 Gold	MPW-7001-ACAAG-EU	R	Rp 1.317.000	80Plus Gold	Non Modular	2	6	4	3	120mm Hydrodynamic fan bearing	5 Years
PSU G600 Gold	MPW-6001-ACAAG-EU	R	Rp 1.106.000	80Plus Gold	Non Modular	2	6	4	3	120mm Hydrodynamic fan bearing	5 Years
PSU MWE Gold 1250W V2 UK	MPE-C501-AFCAG	R	Rp 3.540.000	80Plus Gold	Non Modular	2	12	8	4	140mm Fan	10 Years
PSU MWE Gold 1250W V2	MPE-C501-AFCAG	R	Rp 3.540.000	80Plus Gold	Non Modular	2	12	8	4	140mm Fan	10 Years
PSU MWE Gold 1050W V2	MPE-A501-AFCAG	R	Rp 2.926.000	80Plus Gold	Non Modular	2	12	6	4	140mm Fan	10 Years
PSU MWE Bronze 550 V2	MPE-5501-ACAAB	R	Rp 727.000	80 Plus Bronze	Non Modular	1	6	4	4	120mm HDB Fan	5 Years
PSU MWE Bronze 650 V2	MPE-6501-ACAAB	R	Rp 881.000	80 Plus Bronze	Non Modular	2	8	4	4	120mm HDB Fan	5 Years
PSU MWE Bronze 750 V2	MPE-7501-ACAAB	R	Rp 1.055.000	80 Plus Bronze	Non Modular	2	8	4	4	120mm HDB Fan	5 Years
PSU Elite V4 White 500	MPE-5001-ACABN	R	Rp 586.000	80 Plus White 230V	Non Modular	1	5	2	2	120 mm Fan	3 Years
PSU Elite V4 White 600	MPE-6001-ACABN	R	Rp 681.000	80 Plus White 230V	Non Modular	1	5	2	3	120 mm Fan	3 Years
MasterWatt 1500 Maker 80+Titanium A/UK	MPZ-F001-AFBAT-U1	NA	Rp 4.980.000	80 Plus Titanium	Full Modular	2	5	8	3	135 mm Fan	7 Year
MWE Gold 650 80+ Gold Full Modular	MPY-6501-AFAAG-EU	R	Rp 1.550.000	80 Plus Gold	Full Modular	1	8	4	6	120 mm Fan	5 Years
MWE Gold 550 80+ Gold Full Modular	MPY-5501-AFAAG-EU	R	Rp 1.273.000	80 Plus Gold	Full Modular	1	8	2	3	120 mm Fan	5 Years
Elite V3 P500	MPW-5001-PCABN1	R	Rp 549.000	None 80Plus	Non Modular	1	3	1	2	120mm Sleeve Bearing	3 Years

SFX Series

Product	Part No.	Stock	MSRP	Certification	Modularity	CPU 4+4 Pin	SATA Connector	PCI Express Connector	4-Pin Molex	Fan	Warranty
CMT PSU V850 SFX Gold	MPY-8501-SFHAGV	R	Rp 2.351.000	80 Plus Gold	Full Modular	2	8	4	4	92mm	5 Years
CMT PSU V750 SFX Gold	MPY-7501-SFHAGV	R	Rp 1.598.000	80 Plus Gold	Full Modular	2	8	4	4	92mm	5 Years
CMT PSU V650 SFX Gold	MPY-6501-SFHAGV	R	Rp 1.399.000	80 Plus Gold	Full Modular	2	8	4	4	92mm	5 Years

Product	Part No.	Stock	MSRP	Dimension	Output Power	Efficiency	Protections	Input Voltage	Operation Temperature	Fan	Warranty
Extension Cable Red Black	CMA-SEST16RDBK1-GL	R	Rp 323.000	30cm	16 AWG	Single Sleeve	Red & black Sleeve	4x 24 Pin, 12x 8 Pin, 8x 6 Pin		1x 24 Pin, 1x 8(4+4) Pin, 2x PCI-e 6 Pin, 2x PCI-e 8 Pin	
Extension Cable Blue Black	CMA-SEST16BLBK1-GL	R	Rp 323.000	30cm	16 AWG	Single Sleeve	Blue & black Sleeve	4x 24 Pin, 12x 8 Pin, 8x 6 Pin		1x 24 Pin, 1x 8(4+4) Pin, 2x PCI-e 6 Pin, 2x PCI-e 8 Pin	
Extension Cable White Black	CMA-SEST16WTBK1-GL	C	Rp 323.000	30cm	16 AWG	Single Sleeve	White & black Sleeve	4x 24 Pin, 12x 8 Pin, 8x 6 Pin		1x 24 Pin, 1x 8(4+4) Pin, 2x PCI-e 6 Pin, 2x PCI-e 8 Pin	
Extension Cable Green Black	CMA-SEST16GRBK1-GL	R	Rp 323.000	30cm	16 AWG	Single Sleeve	Green & black Sleeve	4x 24 Pin, 12x 8 Pin, 8x 6 Pin		1x 24 Pin, 1x 8(4+4) Pin, 2x PCI-e 6 Pin, 2x PCI-e 8 Pin	

CPU Liquid Cooling System

Product	Part No.	Stock	MSRP	Socket Compatibility	Radiator Dimension	Warranty	Remark
MasterLiquid							
MasterLiquid ML360 SUB-ZERO	MLZ-D36M-A19PK-12	L	Rp 5.587.000	(Only) Intel LGA 1200 with supporting Intel Cryo Motherboard !	394 x 119.6 x 27.2 mm / 15.5 x 4.7 x 1.1 inch	5 Years	PUMP DIMENSIONS 57.3 x 57.3 x 92.2 mm / 2.3 x 2.3 x 3.6 inch PUMP MTTF 198,000 Hours PUMP NOISE LEVEL < 35 dBA POWER CONNECTOR 4-Pin PUMP RATED VOLTAGE 12 VDC PUMP RATED CURRENT 1.0 A PUMP POWER CONSUMPTION 13.8W (Max) FAN DIMENSIONS (L X W X H) 120 x 120 x 25 mm / 4.7 x 4.7 x 1 inch FAN QUANTITY 3 PCS FAN SPEED 650-1900 RPM ± 10% FAN AIRFLOW 59 CFM (Max) FAN NOISE LEVEL 8 - 26 dBA FAN PRESSURE 2.0 mmH ₂ O (Max) TOTAL POWER CONSUMPTION 200 W
MasterLiquid ML360 RGB TR4	MLX-D36M-A20PC-T1	L	Rp 1.699.000	(Only) AMD® Socket TR4	4 x 119 x 27.2mm(15.5 x 4.7 x 1.1 inch)	2 Years	650 ~ 2000 RPM (PWM) ± 10%, Air Flow 66.7 CFM (Max), Air Pressure 2.34 mmH ₂ O (Max) MTTF 160,000 hours, Noise Level 6 ~ 30 dBA, Connector 4-Pin (PWM), Rated Voltage 12 VDC, Pump Dimensions 86 x 70 x 49 mm (3.4 x 2.8 x 1.9"), MTTF 70,000 hours Noise Level < 15 dBA, Connector 3-Pin, Rated Voltage 12 VDC
MasterLiquid PL360 Flux	MLY-D36M-A23PZ-R1	L	Rp 2.930.000	LGA1700*, LGA1200, LGA2066, LGA2011-V3, LGA2011, LGA1151, LGA1150, LGA1155, LGA1156, AM4, AM3+, AM3, AM2, AM2+, FM2+, FM2, FM1, TR4	394 X 119.6 X 27.2MM	5 YEARS	PUMP NOISE LEVEL 15 DBA (MAX) PUMP CONNECTOR 4-PIN (PWM) PUMP RATED VOLTAGE 12 VDC PUMP POWER CONSUMPTION 6W FAN DIMENSIONS (L X W X H) 120 X 120 X 25 MM / 4.7 X 4.7 X 1 INCH FAN QUANTITY 3 PCS FAN LED TYPE ADDRESSABLE GEN 2 RGB FAN SPEED 0-2300 RPM ± 10% FAN AIRFLOW 72.37 CFM (MAX) FAN NOISE LEVEL 32 DBA FAN PRESSURE 2.96 MMH ₂ O (MAX) FAN BEARING TYPE LOOP DYNAMIC BEARING FAN LIFE EXPECTANCY >160,000 HOURS
MasterLiquid PL240 Flux	MLY-D24M-A23PZ-R1	L	Rp 2.240.000	LGA1700*, LGA1200, LGA2066, LGA2011-V3, LGA2011, LGA1151, LGA1150, LGA1155, LGA1156, AM4, AM3+, AM3, AM2, AM2+, FM2+, FM2, FM1, TR4	277 x 119.6 x 27.2mm	5 YEARS	PUMP NOISE LEVEL 15 DBA (MAX) PUMP CONNECTOR 4-PIN (PWM) PUMP RATED VOLTAGE 12 VDC PUMP POWER CONSUMPTION 6W FAN DIMENSIONS (L X W X H) 120 X 120 X 25 MM / 4.7 X 4.7 X 1 INCH FAN QUANTITY 2 PCS FAN LED TYPE ADDRESSABLE GEN 2 RGB FAN SPEED 0-2300 RPM ± 10% FAN AIRFLOW 72.37 CFM (MAX) FAN NOISE LEVEL 32 DBA FAN PRESSURE 2.96 MMH ₂ O (MAX) FAN BEARING TYPE LOOP DYNAMIC BEARING FAN LIFE EXPECTANCY >160,000 HOURS
MasterLiquid ML360 Illusion	MLX-D36M-A18P2-R1	R	Rp 1.913.000	LGA2066, LGA2011-v3, LGA2011, LGA1200, LGA1151, LGA1150, LGA1155, LGA1156, AM4, AM3+, AM3, AM2+, AM2, FM2+, FM2, FM1	394 x 119.6 x 27.2 mm	3 years	PUMP MTTF 70,000 Hours PUMP NOISE LEVEL < 10 dBA PUMP CONNECTOR 3-Pin PUMP RATED VOLTAGE 12 VDC PUMP POWER CONSUMPTION 2.36 W FAN DIMENSIONS (L X W X H) 120 x 120 x 25 mm / 4.7 x 4.7 x 1 inch FAN QUANTITY 3 PCS FAN LED TYPE Addressable Gen 2 RGB FAN SPEED 650-1800 RPM (PWM) ± 10% FAN AIRFLOW 47.2 (Max) FAN NOISE LEVEL 6 - 30 dBA FAN PRESSURE 1.60 mmH ₂ O (Max) FAN LIFE EXPECTANCY 160,000 Hours
MasterLiquid ML360 Mir TR4	MLX-D36M-A18PK-T1	L	Rp 1.747.000	(Only) AMD® Socket TR4 sTRX40/sWRX8	394 x 119 x 27.2 mm	2 Years	PUMP MTTF 70,000 Hours PUMP NOISE LEVEL < 10 dBA PUMP CONNECTOR 3-Pin PUMP RATED VOLTAGE 12 VDC PUMP POWER CONSUMPTION 2.36 W FAN DIMENSIONS (L X W X H) 120 x 120 x 25 mm / 4.7 x 4.7 x 1 inch FAN QUANTITY 3 PCS FAN LED TYPE Non-LED FAN SPEED 650-1800 RPM (PWM) ± 5% FAN AIRFLOW 62 CFM (Max) FAN NOISE LEVEL 8 - 27 dBA FAN PRESSURE 25 mmH ₂ O (Max) FAN LIFE EXPECTANCY 160,000 Hours FAN POWER CONNECTOR 4-Pin (PWM) FAN RATED VOLTAGE 12VDC FAN RATED CURRENT 0.15A TDP 280W
MasterLiquid ML360L ARGB V2	MLW-D36M-A18PA-R2	R	Rp 1.525.000	LGA2066, LGA2011-v3, LGA2011, LGA1200, LGA1151, LGA1150, LGA1155, LGA1156, AM4, AM3+, AM3, AM2+, AM2, FM2+, FM2, FM1	394 x 119.6 x 27.2 mm	2 Years	79.9 x 76 x 47.1 mm / 3.1 x 3 x 1.9 inch, PUMP MTTF, 70,000 Hours, PUMP NOISE LEVEL, < 15 dBA, POWER CONNECTOR, 3-Pin, PUMP RATED VOLTAGE 12 VDC, PUMP POWER CONSUMPTION, 2.36W (LED 2.21W), FAN DIMENSIONS (L X W X H) 120 x 120 x 25 mm / 4.7 x 4.7 x 1 inch, FAN QUANTITY, 3 PCS, FAN LED, Addressable RGB FAN SPEED, 650-1800 RPM ± 10%, FAN AIRFLOW, 62 CFM (Max) FAN NOISE LEVEL, 8 - 27 dBA, FAN PRESSURE, 2.5 mmH ₂ O (Max) FAN LIFE EXPECTANCY, 160,000 Hours, FAN POWER CONNECTOR 4-Pin (PWM), FAN RATED VOLTAGE, 12VDC, FAN RATED CURRENT, 0.15A (LED 0.2A), TDP, 250 W
MasterLiquid ML360R RGB	MLX-D36M-A20PC-R1	R	Rp 1.810.000	Intel® LGA 2066/ 2011-v3 / 2011 / 1151 / 1150 / 1155 / 1156 / 1366 / 775 AMD Socket AM4 / AM3+ / AM3 / AM2+ / AM2 / FM2+ / FM2 / FM1	394 x 119 x 27.2mm	2 Years	20 x 120 x 25 mm (4.7 x 4.7 x 1") Fan Quantity 3 PCS Fan Speed 650 ~ 2000 RPM (PWM) ± 10% Fan Air Flow 66.7 CFM (Max) Fan Air Pressure 2.34 mmH ₂ O (Max) Fan MTTF 160,000 hours Fan Noise Level 6 ~ 30 dBA Fan Connector 4-Pin (PWM) Fan Rated Voltage 12 VDC Pump Dimensions 83.6 x 71.8 x 52.7 mm (3.3 x 2.8 x 2.1") Pump MTTF 70,000 hours Pump Noise Level < 15 dBA Pump Connector 3-Pin Pump Rated Voltage 12 VDC
MasterLiquid ML360L V2 ARGB White	MLW-D24M-A18PW-RW	R	Rp 1.593.000	Intel® LGA 2066/ 2011-v3 / 2011 / 1151 / 1150 / 1155 / 1156 / 1366 / 775 AMD Socket AM4 / AM3+ / AM3 / AM2+ / AM2 / FM2+ / FM2 / FM1	394 x 119 x 27.2mm	2 Years	20 x 120 x 25 mm (4.7 x 4.7 x 1") Fan Quantity 3 PCS Fan Speed 650 ~ 2000 RPM (PWM) ± 10% Fan Air Flow 66.7 CFM (Max) Fan Air Pressure 2.34 mmH ₂ O (Max) Fan MTTF 160,000 hours Fan Noise Level 6 ~ 30 dBA Fan Connector 4-Pin (PWM) Fan Rated Voltage 12 VDC Pump Dimensions 83.6 x 71.8 x 52.7 mm (3.3 x 2.8 x 2.1") Pump MTTF 70,000 hours Pump Noise Level < 15 dBA Pump Connector 3-Pin Pump Rated Voltage 12 VDC
Master Liquid ML240 Illusion White	MLX-D24M-A18PW-R1	R	Rp 1.622.000	Intel® LGA 2066/ 2011-v3 / 2011 / 1151 / 1150 / 1155 / 1156 / 1366 / 775 AMD Socket AM4 / AM3+ / AM3 / AM2+ / AM2 / FM2+ / FM2 / FM1	277 x 119.6 x 27.2 mm	3 years	20 x 120 x 25 mm (4.7 x 4.7 x 1") Fan Quantity 2 PCS Fan Speed 650 ~ 2000 RPM (PWM) ± 10% Fan Air Flow 66.7 CFM (Max) Fan Air Pressure 2.34 mmH ₂ O (Max) Fan MTTF 160,000 hours Fan Noise Level 6 ~ 30 dBA Fan Connector 4-Pin (PWM) Fan Rated Voltage 12 VDC Pump Dimensions 83.6 x 71.8 x 52.7 mm (3.3 x 2.8 x 2.1") Pump MTTF 70,000 hours Pump Noise Level < 15 dBA Pump Connector 3-Pin Pump Rated Voltage 12 VDC
MasterLiquid ML240 Illusion	MLX-D24M-A18P2-R1	R	Rp 1.600.000	Intel® LGA 2066/ 2011-v3 / 2011 / 1151 / 1150 / 1155 / 1156 / 1366 / 775 AMD Socket AM4 / AM3+ / AM3 / AM2+ / AM2 / FM2+ / FM2 / FM1	277 x 119.6 x 27.2 mm	2 Years	20 x 120 x 25 mm (4.7 x 4.7 x 1") Fan Quantity 3 PCS Fan Speed 650 ~ 2000 RPM (PWM) ± 10% Fan Air Flow 66.7 CFM (Max) Fan Air Pressure 2.34 mmH ₂ O (Max) Fan MTTF 160,000 hours Fan Noise Level 6 ~ 30 dBA Fan Connector 4-Pin (PWM) Fan Rated Voltage 12 VDC Pump Dimensions 83.6 x 71.8 x 52.7 mm (3.3 x 2.8 x 2.1") Pump MTTF 70,000 hours Pump Noise Level < 15 dBA Pump Connector 3-Pin Pump Rated Voltage 12 VDC
MasterLiquid ML240L V2 ARGB White	MLW-D24M-A18PW-RW	R	Rp 1.235.000	Intel® LGA 2066/ 2011-v3 / 2011 / 1151 / 1150 / 1155 / 1156 / 1366 / 775 AMD Socket AM4 / AM3+ / AM3 / AM2+ / AM2 / FM2+ / FM2 / FM1	277 x 119.6 x 27.2 mm	2 Years	20 x 120 x 25 mm (4.7 x 4.7 x 1") Fan Quantity 3 PCS Fan Speed 650 ~ 2000 RPM (PWM) ± 10% Fan Air Flow 66.7 CFM (Max) Fan Air Pressure 2.34 mmH ₂ O (Max) Fan MTTF 160,000 hours Fan Noise Level 6 ~ 30 dBA Fan Connector 4-Pin (PWM) Fan Rated Voltage 12 VDC Pump Dimensions 83.6 x 71.8 x 52.7 mm (3.3 x 2.8 x 2.1") Pump MTTF 70,000 hours Pump Noise Level < 15 dBA Pump Connector 3-Pin Pump Rated Voltage 12 VDC

MasterLiquid ML240L ARGB V2	MLW-D24M-A18PA-R2	R	Rp	1.136.000	LGA2066, LGA2011-v3, LGA2011, LGA1200, LGA1151, LGA1150, LGA1155, LGA1156, AM4, AM3+, AM3, AM2+, AM2, FM2+, FM2, FM1	277 x 119.6 x 27.2 mm	2 Years	PUMP DIMENSIONS 79.9 x 76 x 47.1 mm / 3.1 x 3 x 1.9 inch PUMP MTTF 70,000 Hours PUMP NOISE LEVEL < 15 dBA POWER CONNECTOR 3-Pin PUMP RATED VOLTAGE 12 VDC PUMP POWER CONSUMPTION 2.36W (LED 2.21W) FAN DIMENSIONS (L X W X H) 120 x 120 x 25 mm / 4.7 x 4.7 x 1 inch FAN QUANTITY 2 PCS FAN LED Addressable RGB FAN SPEED 650-1800 RPM ± 10% FAN AIRFLOW 62 CFM (Max) FAN NOISE LEVEL 8 - 27 dBA FAN PRESSURE 2.5 mmH ₂ O (Max) FAN LIFE EXPECTANCY 160,000 Hours FAN POWER CONNECTOR 4-Pin (PWM) FAN RATED VOLTAGE 12VDC FAN RATED CURRENT 0.15A (LED 0.2A) TDP 200 W
MasterLiquid ML240L RGB V2	MLW-D24M-A18PC-R2	NA	Rp	1.070.000	Intel LGA2066, LGA2011-v3, LGA2011, LGA1200, LGA1151, LGA1150, LGA1155, LGA1156 AMD Socket AM4, AM3+, AM3, AM2+, AM2, FM2+, FM2, FM1	277 x 119.6 x 27.2 mm	2 Years	PUMP DIMENSIONS 79.9 x 76 x 47.1 mm PUMP MTTF 70,000 Hours PUMP NOISE LEVEL < 15 dBA POWER CONNECTOR 3-Pin PUMP RATED VOLTAGE 12 VDC PUMP POWER CONSUMPTION 2.36W (LED 2.21W) FAN DIMENSIONS (L X W X H) 120 x 120 x 25 mm / 4.7 x 4.7 x 1 inch FAN QUANTITY 1 PCS, 2 PCS FAN LED RGB FAN SPEED 650-1800 RPM ± 10% FAN AIRFLOW 62 CFM (Max) FAN NOISE LEVEL 8 - 27 dBA
MasterLiquid ML120L RGB V2	MLW-D12M-A18PC-R2	R	Rp	846.000	Intel LGA2066, LGA2011-v3, LGA2011, LGA1200, LGA1151, LGA1150, LGA1155, LGA1156 AMD Socket AM4, AM3+, AM3, AM2+, AM2, FM2+, FM2, FM1	157 x 119.6 x 27.2 mm	2 Years	PUMP DIMENSIONS 79.9 x 76 x 47.1 mm PUMP MTTF 70,000 Hours PUMP NOISE LEVEL < 15 dBA POWER CONNECTOR 3-Pin PUMP RATED VOLTAGE 12 VDC PUMP POWER CONSUMPTION 2.36W (LED 2.21W) FAN DIMENSIONS (L X W X H) 120 x 120 x 25 mm / 4.7 x 4.7 x 1 inch FAN QUANTITY 1 PCS, 2 PCS FAN LED RGB FAN SPEED 650-1800 RPM ± 10% FAN AIRFLOW 62 CFM (Max) FAN NOISE LEVEL 8 - 27 dBA
MasterLiquid ML240L RGB	MLW-D24M-A20PC-R1	NA	Rp	989.000	Intel® LGA 2066 / 2011-v3 / 2011 / 1151 / 1150 / 1155 / 1156 / 1366 / 775 socket AMD® AM4 / AM3+ / AM2+ / FM2+ / FM2 / FM1 socket	277 x 119.6 x 27mm	2 Years	Fan Dimensions 120 x 120 x 25 mm (4.7 x 4.7 x 1") Speed 650 ~ 2000 RPM (PWM) ± 10% Air Flow 66.7 CFM (Max) Air Pressure 2.34 mmH ₂ O (Max) MTTF 160,000 hours Noise Level 6 ~ 30 dBA Connector 4-Pin (PWM) Rated Voltage 12 VDC Pump Dimensions 80.3 x 76 x 42.2 mm (3.2 x 3.0 x 1.7") MTTF 70,000 hours Noise Level < 15 dBA Connector 3-Pin Rated Voltage 12 VDC
MasterLiquid ML240R RGB	MLX-D24M-A20PC-R1	NA	Rp	1.488.000	Intel® LGA 2066 / 2011-v3 / 2011 / 1151 / 1150 / 1155 / 1156 / 1366 / 775 socket AMD® AM4 / AM3+ / AM3 / AM2+ / AM2 / FM2+ / FM2 / FM1 socket	277 x 119.6 x 27 mm	2 Years	Fan Dimensions 120 x 120 x 25 mm (4.7 x 4.7 x 1"), Speed 650 ~ 2000 RPM (PWM) ± 10%, Air Flow 66.7 CFM (Max), Air Pressure 2.34 mmH ₂ O (Max), MTTF 160,000 hours, Noise Level 6 ~ 30 dBA, Connector 4-Pin (PWM), Rated Voltage 12 VDC
MasterLiquid Lite 120	MLW-D12M-A20PW-R1	L	Rp	632.000	Intel® LGA 2066 / 2011-v3 / 2011 / 1366 / 1151 / 1150 / 1156 / AMD® AM4 / AM3+ / AM3 / AM2+ / AM2 / FM2+ / FM2 / FM1 socket	62 x 62 x 36.4 mm	2 Years	Fan Dimension 120 x 120 x 25 mm, Fan Speed 650 ~ 2000 RPM (PWM) ± 10%, Fan Air Flow 66.7 CFM ± 10%, Fan Air Pressure 2.34 mmH ₂ O ± 10%, Radiator Material Aluminum
MasterLiquid ML120L RGB	MLW-D12M-A20PC-R1	NA	Rp	799.000	Intel® LGA 2066 / 2011-v3 / 2011 / 1151 / 1150 / 1155 / 1156 / 1366 / 775 socket AMD® AM4 / AM3+ / AM3 / AM2+ / AM2 / FM2+ / FM2 / FM1 socket	157 x 119.6 x 27mm	2 Years	Fan Dimensions 120 x 120 x 25 mm (4.7 x 4.7 x 1"), Speed 650 ~ 2000 RPM (PWM) ± 10% Air Flow 66.7 CFM (Max), Air Pressure 2.34 mmH ₂ O (Max), MTTF 160,000 hours, Noise Level 6 ~ 30 dBA, Connector 4-Pin (PWM), Rated Voltage 12 VDC, Pump Dimensions 80.3 x 76 x 42.2 mm (3.2 x 3.0 x 1.7"), MTTF 70,000 hours, Noise Level < 15 dBA, Connector 3-Pin, Rated Voltage 12 VDC
MasterFan MF120 Halo	MFL-B2DN-18NPA-R1	R	Rp	249.000	120 x 120 x 25 mm	160,000 Hours	2 Years	HALO OF LIGHT Dual Loop Addressable RGB Lighting Silent Cooling Technology Hybrid Fan Blade Design Wide Range of Compatibility Smart Fan Sensor for Jam Protection
MasterFan MF120 Halo White	MFL-B2DW-18NPA-R1	R	Rp	249.000	120 x 120 x 25 mm	160,000 Hours	2 Years	HALO OF LIGHT Dual Loop Addressable RGB Lighting Silent Cooling Technology Hybrid Fan Blade Design Wide Range of Compatibility Smart Fan Sensor for Jam Protection
MasterFan MF120 Halo 3in1	MFL-B2DN-183PA-R1	R	Rp	769.000	120 x 120 x 25 mm	160,000 Hours	2 Years	HALO OF LIGHT Dual Loop Addressable RGB Lighting Silent Cooling Technology Hybrid Fan Blade Design Wide Range of Compatibility Wired ARGB controller
MasterLiquid ML120R RGB	MLX-D12M-A20PC-R1	NA	Rp	1.359.000	Intel® LGA 2066 / 2011-v3 / 2011 / 1151 / 1150 / 1155 / 1156 / 1366 / 775 socket AMD® AM4 / AM3+ / AM3 / AM2+ / AM2 / FM2+ / FM2 / FM1 socket	157 x 119.6 x 27mm	2 Years	Fan Dimensions 120 x 120 x 25 mm, Speed 650 ~ 2000 RPM (PWM) ± 10%, Air Flow 66.7 CFM (Max), Air Pressure 2.34 mmH ₂ O (Max), MTTF 160,000 hours, Noise Level 6 ~ 30 dBA, Connector 4-Pin (PWM), Rated Voltage 12 VDC, Radiator Material Aluminum

CPU Air Cooling System

Product	Part No.	Stock	MSRP	Socket Compatibility	Dimension	Warranty	Remark
---------	----------	-------	------	----------------------	-----------	----------	--------

Wraith Ripper

Wraith Ripper TR4	MAM-D7PN-DWRPS-T1	NA	Rp	1.945.000	TR4	150 x 132.3 x 160.5 mm	2 Years	HEAT SINK MATERIAL, 7 Heat Pipes, Aluminum Fins, LIGHTING LED TYPE Addressable RGB, LIGHTING CONTROL METHOD, Wraith Ripper RGB Software LIGHTING POWER CONNECTOR, SATA Power, LIGHTING INTERFACE USB connector (9-Pin), FAN DIMENSIONS (L X W X H), 120 x 120 x 25 mm / 4.7 x 4.7 x 1 inch FAN QUANTITY, 1 PCS, FAN SPEED, 0-2750 RPM (PWM) ± 10% FAN AIRFLOW, 76.4 CFM (Max), FAN MTTF, 490,000 Hours FAN NOISE LEVEL, 0 - 38 dBA, FAN POWER CONNECTOR, 4-Pin (PWM) FAN RATED VOLTAGE, 12VDC, FAN RATED CURRENT, 0.45A FAN SAFETY CURRENT, 0.6A
-------------------	-------------------	----	----	-----------	-----	------------------------	---------	--

Master Air Maker Series

MasterAir MA624 Stealth	MAM-D6PS-314PK-R1	R	Rp	1.469.000	LGA2066, LGA2011-v3, LGA2011, LGA1200, LGA1366, LGA1156, LGA1155, LGA1151, LGA1150, AM4, AM3+, AM3, AM2+, AM2, FM2+, FM2, FM1	144.9 x 153.2 x 160 mm	5 Years	HEAT SINK MATERIAL 6 Heat Pipes, Aluminum Fins FAN DIMENSIONS (L X W X H) 140 mm Fan - 140 x 140 x 25 mm / 5.5 x 5.5 x 1 inch, 120 mm Fan - 120 x 120 x 25 mm / 4.7 x 4.7 x 1 inch FAN QUANTITY 140 mm Fan - 2 PCS, 120 mm Fan - 1 PC FAN SPEED 140 mm Fan - 650-1400 RPM ± 5%, 120 mm Fan - 650-1800 RPM ± 5% FAN AIRFLOW 140 mm Fan - 67 CFM (Max), 120 mm Fan - 62 CFM (Max) FAN NOISE LEVEL 140 mm Fan - 10 ~ 27 dBA, 120 mm Fan - 8 ~ 27 dBA FAN AIR PRESSURE 140 mm Fan - 2.25 mmH ₂ O (Max), 120 mm Fan - 2.5 mmH ₂ O (Max) FAN MTTF 160,000 Hours
-------------------------	-------------------	---	----	-----------	---	------------------------	---------	---

MasterAir MA612 Stealth	MAP-T6PS-218PA-R1	R	Rp	1.157.000	LGA2066, LGA2011-v3, LGA2011, LGA1200, LGA1366, LGA1156, LGA1155, LGA1151, LGA1150, AM4, AM3+, AM3, AM2+, AM2, FM2+, FM2, FM1	144.9 x 153.2 x 160 mm	5 Years	HEAT SINK MATERIAL 6 Heat Pipes, Aluminum Fins FAN DIMENSIONS (L X W X H) 140 mm Fan - 140 x 140 x 25 mm / 5.5 x 5.5 x 1 inch, 120 mm Fan - 120 x 120 x 25 mm / 4.7 x 4.7 x 1 inch FAN QUANTITY 140 mm Fan - 2 PCS, 120 mm Fan - 1 PC FAN SPEED 140 mm Fan - 650-1400 RPM ± 5%, 120 mm Fan - 650-1800 RPM ± 5% FAN AIRFLOW 140 mm Fan - 67 CFM (Max), 120 mm Fan - 62 CFM (Max) FAN NOISE LEVEL 140 mm Fan - 10 ~ 27 dBA, 120 mm Fan - 8 ~ 27 dBA FAN AIR PRESSURE 140 mm Fan - 2.25 mmH2O (Max), 120 mm Fan - 2.5 mmH2O (Max) FAN MTTF 160,000 Hours
MasterAir MA612 StealthARGB	MAP-T6PS-218PA-R1	R	Rp	1.223.000	LGA2066, LGA2011-v3, LGA2011, LGA1200, LGA1366, LGA1156, LGA1155, LGA1151, LGA1150, AM4, AM3+, AM3, AM2+, AM2, FM2+, FM2, FM1	129 x 112.2 x 158 mm	5 Years	HEAT SINK MATERIAL 6 Heat Pipes, Aluminum Fins FAN DIMENSIONS (L X W X H) 120 x 120 x 25 mm / 4.7 x 4.7 x 1 inch FAN QUANTITY 2 PCS FAN SPEED 650-1800 RPM (PWM) ± 5% FAN AIRFLOW 62 CFM (Max) FAN NOISE LEVEL 8 - 27 dBA FAN AIR PRESSURE 2.25 mmH2O (Max) FAN MTTF 160,000 Hours
MasterAir MA610P ARGB	MAP-T6PN-218PA-R1	R	Rp	961.000	LGA2066, LGA2011-v3, LGA2011, LGA1200, LGA1366, LGA1156, LGA1155, LGA1151, LGA1150, AM4, AM3+, AM3, AM2+, AM2, FM2+, FM2, FM1	130.9 x 112.8 x 170.4 mm	2 Years	HEAT SINK MATERIAL 6 Heat Pipes, Aluminum Fins FAN DIMENSIONS (L X W X H) 120 x 120 x 25 mm / 4.7 x 4.7 x 1 inch FAN QUANTITY 2 PCS FAN SPEED 650-1800 RPM ± 5% FAN AIRFLOW 62 CFM (Max) FAN NOISE LEVEL 8 - 27 dBA FAN AIR PRESSURE 2.52 mmH2O FAN MTTF 160,000 Hours
MasterAir MA620M	MAM-D6PN-120PA-R1	NA	Rp	1.255.000	Intel Socket : LGA2066, LGA2011-v3, LGA2011, LGA1151, LGA1150, LGA1155, LGA1156 AMD Socket : AM4, AM3+, AM3, AM2+, AM2, FM2+, FM2, FM1	135 x 125 x 165 mm	5 Years	Heatsink Material 6 Heat Pipes, Aluminum Fins FAN QUANTITY 1 PCS FAN SPEED 650-2000 RPM (PWM) ± 10% FAN AIRFLOW 57.3 CFM (Max) FAN AIR PRESSURE 2.0 mmH2O (Max) FAN MTTF 160,000 Hours FAN NOISE LEVEL 8 - 30 dBA
MasterAir MA620P	MAP-D6PN-218PC-R1	NA	Rp	762.000	Intel® LGA 2066 / 2011-3 / 2011 / 1156 / 1155 / 1151 / 1150 / 1366 / 775 socket AMD® AM4* / AM3+ / AM3 / AM2+ / AM2 / FM2+ / FM2 / FM1 socket	122.3 x 112.8 x 166.5 mm	2 Years	Heat Sink Material 6 Heat Pipes / Direct Contact / Aluminum Fins Weight 616g (1.35lb.) Heat Pipe Dimensions Ø6 mm Fan Dimensions 120 x 120 x 25 mm (4.7 x 4.7 x 1") Fan Speed 600 – 1,800 RPM (PWM) ± 10%, Fan Air Flow 53.38 CFM (Max) Fan Air Pressure 1.65mm H2O (Max), Fan MTTF 40,000 hours, LED Color RGB ready Fan Noise Level 35 dBA (Max), Fan Connector 4-Pin
MasterAir MA620P TUF Gaming Edition	MAP-D6PN-AFNPC-R1	NA	Rp	784.000	Intel® LGA 2066 / 2011-3 / 2011 / 1156 / 1155 / 1151 / 1150 / 1366 / 775 socket AMD® AM4* / AM3+ / AM3 / AM2+ / AM2 / FM2+ / FM2 / FM1 socket	122.3 x 112.8 x 166.5 mm	5 Years	Heat Sink Material 6 Heat Pipes / Direct Contact / Aluminum Fins Weight 616g (1.35lb.) Heat Pipe Dimensions Ø6 mm Fan Dimensions 120 x 120 x 25 mm (4.7 x 4.7 x 1") Fan Speed 600 – 1,800 RPM (PWM) ± 10%, Fan Air Flow 53.38 CFM (Max) Fan Air Pressure 1.65mm H2O (Max), Fan MTTF 40,000 hours, LED Color RGB ready Fan Noise Level 35 dBA (Max), Fan Connector 4-Pin
MasterAir MA610P	MAP-T6PN-218PC-R1	NA	Rp	740.000	Intel® LGA 2066 / 2011-3 / 2011 / 1156 / 1155 / 1151 / 1150 / 1366 / 775 socket AMD® AM4* / AM3+ / AM3 / AM2+ / AM2 / FM2+ / FM2 / FM1 socket	122.3 x 112.8 x 166.5 mm (4.8 x 4.4 x 6.5")	2 Years	Heat Sink Material 6 Heat Pipes / Direct Contact / Aluminum Fins Weight 616g (1.35lb.) Heat Pipe Dimensions Ø6 mm Fan Dimensions 120 x 120 x 25 mm (4.7 x 4.7 x 1") Fan Speed 600 – 1,800 RPM (PWM) ± 10%, Fan Air Flow 53.38 CFM (Max) Fan Air Pressure 1.65mm H2O (Max), Fan MTTF 40,000 hours, LED Color RGB ready Fan Noise Level 35 dBA (Max), Fan Connector 4-Pin
MasterAir MA410P	MAP-T4PN-220PC-R1	NA	Rp	592.000	Intel® LGA 2066 / 2011-3 / 2011 / 1156 / 1155 / 1151 / 1150 / 1366 / 775 socket AMD® AM4* / AM3+ / AM3 / AM2+ / AM2 / FM2+ / FM2 / FM1 socket	84 x 129 x 158.5 mm	2 Years	Heat Sink Material 4 Heat Pipes / CDC 2.0 / Aluminum Fins Weight 420 g (0.93 lb.) Heat Pipes Dimensions Ø6mm, Fan Dimensions 120 x 120 x 25 mm (4.7 x 4.7 x 1 inch) Fan Speed 650 – 2,000 RPM (PWM) ± 10%, Fan Air Flow 66.7 CFM (Max) Fan Air Pressure 2.34 mmH2O (Max), Fan MTTF 160,000 hours, Fan Noise Level 6 – 30 dBA Fan Connector 4-Pin (PWM)
MasterAir MA410M	MAM-T4PN-218PC-R1	C	Rp	826.000	Intel® LGA 2066 / 2011-3 / 2011 / 1156 / 1155 / 1151 / 1150 / 1366 / 775 socket AMD® AM4* / AM3+ / AM3 / AM2+ / AM2 / FM2+ / FM2 / FM1 socket	111.8 x 130.9 x 165.1 mm	5 Years	Heat Sink Material 4 Heat Pipes / CDC 2.0 / Aluminum Fins, Heat Sink Weight 820 g (1.8 lb.) Heat Pipes Dimensions Ø6mm, Fan Dimensions 120 x 120 x 25 mm (4.7 x 4.7 x 1 inch) Fan Speed 650 – 1,800 RPM (PWM) ± 10%, Fan Air Flow 53.38 CFM (Max) Fan Air Pressure 1.65 mmH2O (Max), Fan MTTF 40,000 hours, Fan Noise Level 6 – 31 dBA Fan Connector 4-Pin (PWM), Fan Rated Voltage 12 VDC, Fan Rated Current 0.3 A Fan Safety Current 0.37 A, Fan Power Consumption 3.6 W
MasterAir MA410M TUF Edition	MAM-T4PN-AFNPC-R1	NA	Rp	859.000	Intel® LGA 2066 / 2011-3 / 2011 / 1156 / 1155 / 1151 / 1150 / 1366 / 775 socket AMD® AM4* / AM3+ / AM3 / AM2+ / AM2 / FM2+ / FM2 / FM1 socket	111.8 x 130.9 x 165.1 mm	5 Years	Heat Sink Material 4 Heat Pipes / CDC 2.0 / Aluminum Fins, Heat Sink Weight 820 g (1.8 lb.) Heat Pipes Dimensions Ø6mm, Fan Dimensions 120 x 120 x 25 mm (4.7 x 4.7 x 1 inch) Fan Speed 650 – 1,800 RPM (PWM) ± 10%, Fan Air Flow 53.38 CFM (Max) Fan Air Pressure 1.65 mmH2O (Max), Fan MTTF 40,000 hours, Fan Noise Level 6 – 31 dBA Fan Connector 4-Pin (PWM), Fan Rated Voltage 12 VDC, Fan Rated Current 0.3 A Fan Safety Current 0.37 A, Fan Power Consumption 3.6 W
MasterAir G200P	MAP-G2PN-126PC-R1	NA	Rp	510.000	LGA1200, LGA1151, LGA1150, LGA1155, LGA1156, AM4, AM3+, AM3, AM2+, AM2, FM2+, FM2, FM1	95 x 92 x 39.4 mm	2 years	2 Heat Pipes, Aluminum Fins, Copper Plate FAN SPEED 800-2600 RPM (PWM) ± 10% FAN AIRFLOW 35.5 CFM (Max) STATIC PRESSURE 2.4 mm H2O (Max) FAN MTTF 40,000 Hours LED COLOR RGB FAN NOISE LEVEL 6 - 28 dBA FAN POWER CONNECTOR 4-Pin (PWM) FAN RATED VOLTAGE 12VDC FAN RATED CURRENT 0.12A FAN SAFETY CURRENT 0.15A FAN POWER CONSUMPTION 1.44W
MasterAir G100M	MAM-G1CN-924PC-R1	C	Rp	583.000	Intel® LGA 2066 / 2011-3 / 2011 / 1156 / 1155 / 1151 / 1150 / 1366 / 775 socket AMD® AM4* / AM3+ / AM3 / AM2+ / AM2 / FM2+ / FM2 / FM1 socket	145 x 145 x 74.5 mm	2 Years	Heat Sink Material Heat Column / Aluminum Fins Heat Sink Weight 320g (0.70lb.) Heat Column Dimensions Ø41.2*46.3 mm Fan Dimensions 100 x 100 x 25 mm (3.9 x 3.9 x 1 inch) Fan Speed 600~2400 RPM (PWM) ± 10% Fan Airflow 22.63 CFM ± 10% Fan Air Pressure 1.6 mmH2O ± 10% FAN MTTF 280,000 hrs LED color RGB ready Fan Noise Level (dBA) 30 dBA (Max) Fan Connector 4-Pin (PWM) Fan Rated Voltage 12 VDC Fan Rated Current 0.34 A Fan Safety Current 0.37 A Fan Power Consumption 4.08 W
Hyper Series								
Hyper H410R Red Led	RR-H410-20PK-R1	R	Rp	299.000	Intel® LGA 2066 / 2011-3 / 2011 / 1151 / 1150 / 1155 / 1156 / 1366 / 775 socket AMD® AM4 / AM3+ / AM3 / AM2+ / AM2 / FM2+ / FM2 / FM1 socket	102 x 83.4 x 136mm	2 Years	Heat Sink Dimensions 90 x 63.5 x 136mm (3.5 x 2.5 x 5.4 inch) Heat Sink Material 4 Heat Pipes / Direct Contact / Aluminum Fins Heat Sink Weight 358g (0.79lb.)Heat Pipes Dimensions Ø6mm Fan Dimensions 92 x 92 x 25mm (3.6 x 3.6 x 1.0 inch) Fan Speed 600 – 2,000 RPM (PWM) ± 10% Fan Airflow 34.1 CFM ± 10% Fan Air Pressure 1.79mm H2O ± 10% Fan MTTF 40,000 hours LED Color White
Hyper H411R White Led	RR-H411-20PW-R1	R	Rp	299.000	Intel® LGA 2066 / 2011-3 / 2011 / 1151 / 1150 / 1155 / 1156 / 1366 / 775 socket AMD® AM4 / AM3+ / AM3 / AM2+ / AM2 / FM2+ / FM2 / FM1 socket	102 x 83.4 x 136mm	2 Years	Heat Sink Dimensions 90 x 63.5 x 136mm (3.5 x 2.5 x 5.4 inch) Heat Sink Material 4 Heat Pipes / Direct Contact / Aluminum Fins Heat Sink Weight 358g (0.79lb.)Heat Pipes Dimensions Ø6mm Fan Dimensions 92 x 92 x 25mm (3.6 x 3.6 x 1.0 inch) Fan Speed 600 – 2,000 RPM (PWM) ± 10% Fan Airflow 34.1 CFM ± 10% Fan Air Pressure 1.79mm H2O ± 10% Fan MTTF 40,000 hours LED Color White

Hyper H410R RGB	RR-H410-20PC-R1	NA	Rp	381.000	Intel® LGA 2066 / 2011-3 / 2011 / 1151 / 1150 / 1155 / 1156 / 1366 / 775 socket AMD® AM4 / AM3+ / AM3 / AM2+ / AM2 / FM2+ / FM2 / FM1 socket	102 x 83.4 x 136 mm	2 years	FAN SPEED 600-2000 RPM (PWM) ± 10% FAN AIRFLOW 34.1 CFM (Max) FAN AIR PRESSURE 1.79 mmH2O (Max) FAN MTTF 40,000 Hours LED COLOR RGB FAN NOISE LEVEL 6-29 dBA FAN POWER CONNECTOR 4-Pin (PWM) FAN RATED VOLTAGE 12VDC FAN RATED CURRENT 0.24A FAN SAFETY CURRENT 0.4A FAN POWER CONSUMPTION 2.28W WARRANTY 2 years EAN CODE 4719512094679 UPC CODE 884102067099 SERIES Hyper COOLER TYPE Air Cooler HEATPIPS 4
Hyper 212 White LED	RR-212L-16PW-R1	R	Rp	360.000	Intel® LGA 2066 / 2011-3 / 2011 / 1151 / 1150 / 1155 / 1156 / 1366 / 775 socket AMD® AM4 / AM3+ / AM3 / AM2+ / AM2 / FM2+ / FM2 / FM1 socket	120 x 79.5 x 158 mm	2 Years	HEAT SINK MATERIAL 4 Heat Pipes, Aluminum Fins, Direct Contact FAN DIMENSIONS (L X W X H) 120 x 120 x 25 mm / 4.7 x 4.7 x 1 inch FAN QUANTITY 1 PCS FAN SPEED 600-1600 RPM (PWM) ± 10% FAN AIRFLOW 66.3 CFM (Max) FAN AIR PRESSURE 1.7 mmH2O FAN MTTF 40,000 Hours FAN NOISE LEVEL 9 - 31 dBA
Hyper 212 LED Turbo ARGB	RR-212TK-18PA-R1	R	Rp	664.000	Intel® LGA 2066 / 2011-3 / 2011 / 1151 / 1150 / 1155 / 1156 / 1366 / 775 socket AMD® AM4 / AM3+ / AM3 / AM2+ / AM2 / FM2+ / FM2 / FM1 socket	120 x 79.5 x 158 mm	2 Years	HEAT SINK MATERIAL 4 Heat Pipes, Aluminum Fins, Direct Contact FAN DIMENSIONS (L X W X H) 120 x 120 x 25 mm / 4.7 x 4.7 x 1 inch FAN QUANTITY 1 PCS FAN SPEED 600-1600 RPM (PWM) ± 10% FAN AIRFLOW 66.3 CFM (Max) FAN AIR PRESSURE 1.7 mmH2O FAN MTTF 40,000 Hours FAN NOISE LEVEL 9 - 31 dBA
Hyper 212 White LED Turbo	RR-212TW-16PW-R1	R	Rp	514.000	LGA2066, LGA2011-v3, LGA2011, LGA1151, LGA1150, LGA1155, LGA1156, LGA1366, AM4, AM3+, AM3, AM2+, AM2, FM2+, FM2, FM1	120 x 120 x 25 mm	2 Years	
Hyper 212 RGB Black Ed 1700		R	Rp	778.000	LGA1700,LGA2066, LGA2011-v3, LGA2011, LGA1151, LGA1150, LGA1155, LGA1156, LGA1366, AM4, AM3+, AM3, AM2+, AM2, FM2+, FM2, FM1	120 x 120 x 25 mm	2 Years	HEAT SINK MATERIAL 4 Heat Pipes, Aluminum Fins, Direct Contact FAN DIMENSIONS (L X W X H) 120 x 120 x 25 mm / 4.7 x 4.7 x 1 inch FAN QUANTITY 1 PCS FAN SPEED 650-2000 RPM (PWM) ± 10% FAN AIRFLOW 59 CFM (Max) FAN AIR PRESSURE 2.1 mmH2O FAN MTTF 160,000 Hours FAN NOISE LEVEL 8 - 30 dBA
Hyper 212 RGB Black Edition	RR-212S-20PC-R1	NA	Rp	756.000	LGA2066, LGA2011-v3, LGA2011, LGA1151, LGA1150, LGA1156, LGA1155, LGA1366, AM4, AM3+, AM3, AM2+, AM2, FM2+, FM2, FM1	120 x 79.6 x 158.8 mm	2 Years	
Hyper 212 LED Turbo Black Top Cover	RR-212TK-16PR-R1	C	Rp	438.000	Intel® LGA 2011-3 / 2011 / 1156 / 1155 / 1151 / 1150 / 775 socket AMD® AM4 / AM3+ / AM3 / AM2+ / FM2+ / FM2 / FM1 socket	120 x 108 x 163 mm	2 Years	Speed 600-1,600 RPM ± 10% Airflow 66.3 CFM ± 10% Air Pressure 1.7 mmH2O ± 10% MTTF 40,000 hours
Hyper 212 LED Turbo Red Top Cover	RR-212TR-16PR-R1	R	Rp	438.000	Intel® LGA 2011-3 / 2011 / 1156 / 1155 / 1151 / 1150 / 775 socket AMD® AM4 / AM3+ / AM3 / AM2+ / FM2+ / FM2 / FM1 socket	120 x 108 x 163 mm	2 Years	Air Pressure 1.7 mmH2O ± 10% MTTF 40,000 hours
Hyper 212 LED	RR-212L-16PR-R1	R	Rp	332.000	Intel® LGA 2011-3 / 2011 / 1156 / 1155 / 1151 / 1150 / 775 socket AMD® AM4* / AM3+ / AM3 / AM2+ / FM2+ / FM2 / FM1 socket	120(L) x 84(W) x 160(H) mm	2 Years	Fan Speed 600-1,600 RPM ± 10%, Fan Airflow 66.3 CFM ± 10%
Hyper T20	RR-T20-20FK-R1	R	Rp	189.000	LGA1156, LGA1155, LGA1151, LGA1150, LGA775, AM4, AM3+, AM3, AM2, FM2+, FM2, FM1	95 x 80 x 117 mm		
Blizzard / Other Series								
I30	RH-I30-26FK-R1	R	Rp	69.000	Intel® LGA 1156 / 1155 / 1151 / 1150 socket	95 x 95 x 55 mm	2 Years	Fan Dimensions 92 x 92 x 25 mm (3.6 x 3.6 x 1.0 inch) Fan Speed 2,600 RPM ± 10% Fan Airflow 31 CFM ± 10% Air Pressure 2.21 mm H2O ± 10% Noise Level 28 dBA(Max) Bearing Rifle MTTF 280,000 hours L-10 Life 40,000 hours Fan Connector 3-Pin Fan Rated Voltage 12 VDC Fan Rated Current 0.13A Power Consumption 1.56 W
CLR A71C ARGB	RR-A71C-18PA-R1	R	Rp	292.000	AM4	120 x 120 x 60 mm 4.7 x 4.7 x 2.36 inch	2 Years	SUPPORT SOCKET AM4 WIDE RPM RANGE PWM FAN WITH ARGB LIGHTING DIRECT CONTACT COPPER CORE
I70C	RR-I70C-20PK-R1	R	Rp	162.000	Intel® LGA 1156 / 1155 / 1151 / 1150 socket	120 x 120 x 60 mm	2 Years	Fan Dimensions 120 x 120 x 25 mm (4.7 x 4.7 x 1.0 inch) Fan Speed 1,800 RPM ± 10% Fan Airflow 37 CFM ± 10% Air Pressure 1.33 mm H2O ± 10% Noise Level 28 dBA(Max) Bearing Rifle MTTF 280,000 hours L-10 Life 40,000 hours Fan Connector 4-Pin Fan LED Blue Fan Rated Voltage 12 VDC Fan Rated Current 0.2 A Power Consumption 2.4 W

CHASSIS FAN								
Product	Part No.	Stock	MSRP	Dimension	Life Expectancy	Warranty	Remark	
MASTERFAN SERIES								
MasterFan MF120 Prism 3in1	MFY-B2DN-203PA-R1	R	Rp 841.000	120 x 120 x 25 mm	160,000 Hours	2 Years	FAN PROFILE Addressable RGB FAN BEARING TYPE Rifle Bearing FAN SPEED 650-2000 RPM ± 5% FAN AIRFLOW 55 CFM (Max) FAN AIR PRESSURE 2.91 mmH2O (Max) FAN NOISE LEVEL 8 - 27 dBA FAN DIMENSIONS (L X W X H) 120 x 120 x 25 mm / 4.7 x 4.7 x 1 inch FAN MTTF 160,000 Hours RGB CONNECTOR 3-Pin ARGB RGB RATED VOLTAGE 5V DC RGB RATED CURRENT 0.65A FAN RATED VOLTAGE 12VDC FAN RATED CURRENT 0.12A FAN SAFETY CURRENT 0.37A FAN POWER CONSUMPTION 1.44W FAN POWER CONNECTOR 4-Pin (PWM)	
MasterFan MF120 Prismatic	MFY-B2DN-20NPA-R1	R	Rp 313.000	120 x 120 x 25 mm	160,000 Hours	2 Years	FAN PROFILE Addressable RGB FAN SPEED 650-1800 RPM ± 10% FAN AIRFLOW 47.2 CFM ± 10% FAN AIR PRESSURE 1.6 mmH2O ± 10% FAN NOISE LEVEL 6 - 30 dBA FAN MTTF 160,000 Hours FAN BEARING TYPE Rifle Bearing FAN CONNECTOR 4-Pin	
MasterFan MF120 Halo 3in1 White	MFL-B2DW-183PA-R1	R	Rp 830.000	120 x 120 x 25 mm	160,000 Hours	2 Years	PROFILE Addressable RGB FAN SPEED 650-1500 RPM FAN AIRFLOW 55 CFM ± 10% FAN AIR PRESSURE 1.17 mmH2O ± 10% FAN NOISE LEVEL 6 - 30 dBA FAN DIMENSIONS (L X W X H) 140 x 140 x 25 mm / 5.5 x 5.5 x 1 inch FAN MTTF 160,000 Hours FAN BEARING TYPE Rifle Bearing	
MasterFan MF140 Halo	MFL-B4DN-15NPA-R1	L	Rp 271.000	140 x 140 x 25 mm	160,000 Hours	2 Years	PROFILE Addressable RGB FAN SPEED 650-1500 RPM FAN AIRFLOW 55 CFM ± 10% FAN AIR PRESSURE 1.17 mmH2O ± 10% FAN NOISE LEVEL 6 - 30 dBA FAN DIMENSIONS (L X W X H) 140 x 140 x 25 mm / 5.5 x 5.5 x 1 inch FAN MTTF 160,000 Hours FAN BEARING TYPE Rifle Bearing	

MasterFan Pro 140 AF RGB 3 in 1 with Controller	MFY-F4DC-083PC-R1	NA	Rp	899.000	140 x 140 x 25 mm	490,000 Hours	5 Years	Fan Speed 650-1,550 RPM ± 10%, Air Flow 46.2 CFM ± 10%, Air Pressure 1.59 mmH2O ± 10% Noise Level 6 - 20 dBA, MTTF 490,000 Hours, L-10 Life 70,000 Hours, Fan Connector 4-Pin Rated Voltage 12 VDC, Rated Current 0.22 A, Safety Current 0.4 A, Power Consumption 3.84 W Weight 172 g
MasterFan Pro 140 AP RGB 3 in 1 with Controller	MFY-P4DC-153PC-R1	C	Rp	899.000	140 x 140 x 25 mm	490,000 Hours	5 Years	
MasterFan MF120R ARGB	R4-120R-20PC-R1	NA	Rp	211.000	120 x 120 x 25 mm	490,000 Hours	5 Years	Product Name MasterFan MF120R ARGB 3in1 Product Number R4-120R-203C-R1 Profile ARGB Bearing Type Rifle Fan Speed (RPM) 650~2000 ± 10% Airflow (CFM) 59 ± 10% Air Pressure (mmH2O) 2.14 Fan Noise Level (dBA) 31 Dimensions (mm) 120 x 120 x 25 (4.7 x 4.7 x 1") MTTF (hours) 280,000 L-10 Life (hours) 40,000 RGB Rated Voltage 5 VDC RGB Rated Current 0.34A Rated Voltage 12 VDC Rated Current 0.2A Safety Current 0.54A Connector 4-Pin Weight 137g x 3 Warranty 2 years
MasterFan SF120M	MFZ-B2NN-20NPK-R1	L	Rp	377.000	120 x 120 x 25 mm	280,000 Hours	5 Years	MasterFan SF120M is an innovation leading fan from Cooler Master that comes with patented anti-vibration motor and damping frame design. The performance, stability, and durability of this fan comes from the industrial grade materials used during the production process. The double ball-bearing reduces the rotational friction for enhanced performance and longevity of the fan. Premium metallic shields are integrated into the fan frame for an industrial grade toughness to the fan. Along with multi-fan connection design and fan speed control, the SF120M is the obvious choice for performance and durability.
MasterFan SF360R ARGB	MFX-B2D3-18NPA-R1	NA	Rp	595.000	360 x 120 x 25 mm	160,000 Hours	2 Years	Fan Speed : 650-1800 RPM ± 10% Fan Airflow : 43 x 3 CFM ± 10% Fan Air Pressure : 1.58 mmH2O ± 10%
MasterFan SF240R ARGB	MFX-B2D2-18NPA-R1	L	Rp	399.000	240 x 120 x 25 mm	160,000 Hours	2 Years	Fan Speed : 650-1800 RPM ± 10% Fan Airflow : 43 x 2 CFM ± 10% Fan Air Pressure : 1.58 mmH2O ± 10%
MasterFan SF120R ARGB	MFX-B2DN-20NPA-R1	NA	Rp	199.000	120 x 120 x 25 mm	160,000 Hours	2 Years	Fan Speed : 650-2000 RPM (PWM) ± 10% Fan Airflow : 59 CFM ± 10% Fan Air Pressure : 2.1 mmH2O ± 10%
MasterFan Pro 120AP RGB	MFY-P2DN-15NPC-R1	C	Rp	275.000	120 x 120 x 25 mm	490,000 hours	5 Years	Profile R Mode (Red), B Mode (Blue), RGB Mode (RGB Ready), Fan Speed : 650 - 2750 RPM (PWM) ± 10%. Air Flow : 35 - 62.1 CFM ± 10%. Air Pressure : 1.45 - 4.6 mmH2O ± 10%
MasterFan Pro 120 Air Balance RGB	MFY-B2DN-13NPC-R1	NA	Rp	222.000				Fan Speed : 650 -1300 RPM (PWM) ± 10%. Air Flow : 42.7 CFM ± 10%. Air Pressure : 0.96 mmH2O ± 10%
Masterfan MF120R A-RGB 3in 1		NA	Rp	699.000				
MasterFan MF120L RGB	R4-C1DS-12FC-R1	NA	Rp	122.000				Profile Red, Blue, RGB, Dimensions 120 x 120 x 25 mm(4.7 x 4.7 x 1 inch), Fan Speed 650-1,100 RPM ± 10%, Air Flow 48.8 CFM ± 10%, Air Pressure 0.88 mmH2O ± 10%, Noise Level 6 - 20 dBA
MasterFan MF120L Red	R4-C1DS-12FR-R1	C	Rp	99.000				Dimensions 120 x 120 x 25 mm(4.7 x 4.7 x 1 Inch), Fan Speed 650-1,100 RPM ± 10%, Air Flow 48.8 CFM ± 10%, Air Pressure 0.88 mmH2O ± 10%, Noise Level 6 - 20 dBA
MasterFan MF120L White	R4-C1DS-12FW-R1	NA	Rp	99.000				
MasterFan MF120L Blue	R4-C1DS-12FB-R1	NA	Rp	99.000				
MasterFan MF120R RGB	R4-C1DS-20PC-R1	NA	Rp	148.000	120 x 120 x 25 mm	280.000 hours	2 Years	Fan Speed (RPM) 650 ~ 2,000 ± 10%, Airflow (CFM) 59 ± 10%, Air Pressure (mmH2O) 2.14, Fan Noise Level 31 DbA
MasterFan MF200R ARGB		NA	Rp	299.000				
MasterFan MF200R RGB	R4-200R-08FC-R1	NA	Rp	378.000	200 x 200 x 25 mm	175.000 hours	2 Years	Fan Speed (RPM) 800 ± 150 Airflow (CFM) 90 ± 10% Air Pressure (mmH2O) 0.88 Fan Noise Level 28 dbA
SICKLEFLOW SERIES								
SickleFlow 120 ARGB Reverse	MFX-B2DR-18NPA-R1	R	Rp	158.000	120 x 120 x 25 mm	160,000 Hours	2 Years	FAN PROFILE Addressable RGB FAN BEARING TYPE Rifle Bearing FAN SPEED 650-1800 RPM ± 5% FAN AIRFLOW 62 CFM (Max) FAN AIR PRESSURE 2.5 mmH2O (Max) FAN NOISE LEVEL 8 - 27 dBA FAN MTTF 160,000 Hours RGB CONNECTOR 3-Pin ARGB RGB RATED VOLTAGE 5V DC RGB RATED CURRENT 0.21A FAN RATED VOLTAGE 12VDC FAN RATED CURRENT 0.15A FAN SAFETY CURRENT 0.37A FAN POWER CONSUMPTION 1.8W FAN POWER CONNECTOR 4-Pin (PWM)
SickleFlow 140 ARGB	MFX-B4DN-14NPA-R1	R	Rp	191.000	140 x 140 x 25 mm	160,000 Hours	2 Years	FAN PROFILE Addressable RGB FAN BEARING TYPE Rifle Bearing FAN SPEED 650-1400 RPM ± 200 RPM FAN AIRFLOW 67 CFM ± 10% FAN AIR PRESSURE 2.2 mmH2O ± 10% FAN NOISE LEVEL 10 - 27 dBA FAN DIMENSIONS (L X W X H) 140 x 140 x 25 mm / 5.5 x 5.5 x 1 inch FAN MTTF 160,000 Hours RGB CONNECTOR 3-Pin ARGB RGB RATED VOLTAGE 5V DC RGB RATED CURRENT 0.21A FAN RATED VOLTAGE 12VDC FAN RATED CURRENT 0.15A FAN SAFETY CURRENT 0.4A FAN POWER CONSUMPTION 1.8W FAN POWER CONNECTOR 4-Pin (PWM)
SickleFlow 120 ARGB	MFX-B2DN-18NPA-R1	R	Rp	154.000	120 x 120 x 25 mm	160,000 Hours	2 Years	FAN SPEED 650-1800 RPM ± 10% FAN AIRFLOW 62 CFM ± 10% FAN AIR PRESSURE 2.5 mmH2O ± 10% FAN NOISE LEVEL 8 - 27 dBA RGB CONNECTOR 3-Pin ARGB RGB RATED VOLTAGE 5V DC FAN POWER CONNECTOR 4-Pin (PWM) FAN WEIGHT 156g / 0.34 lbs
SickleFlow 120 ARGB 3in1	MFX-B2DN-183PA-R1	R	Rp	499.000	120 x 120 x 25 mm	160,000 Hours	2 Years	FAN SPEED 650-1800 RPM ± 10% FAN AIRFLOW 62 CFM ± 10% FAN AIR PRESSURE 2.5 mmH2O ± 10% FAN NOISE LEVEL 8 - 27 dBA RGB CONNECTOR 3-Pin ARGB RGB RATED VOLTAGE 5V DC FAN POWER CONNECTOR 4-Pin (PWM) FAN WEIGHT 156g / 0.34 lbs
SickleFlow 120 White	MFX-B2DN-18NPW-R1	R	Rp	96.000	120 x 120 x 25 mm	160,000 Hours	2 years	FAN BEARING TYPE Rifle Bearing FAN SPEED 650-1800 RPM ± 10% FAN AIRFLOW 62 CFM ± 10% FAN AIR PRESSURE 2.5 mmH2O ± 10% FAN NOISE LEVEL 8 - 27 dBA
SickleFlow 120 Blue	MFX-B2DN-18NPB-R1	C	Rp	96.000	120 x 120 x 25 mm	160,000 Hours	2 years	FAN BEARING TYPE Rifle Bearing FAN SPEED 650-1800 RPM ± 10% FAN AIRFLOW 62 CFM ± 10% FAN AIR PRESSURE 2.5 mmH2O ± 10% FAN NOISE LEVEL 8 - 27 dBA
SickleFlow 120 Red	MFX-B2DN-18NPR-R1	C	Rp	96.000	120 x 120 x 25 mm	160,000 Hours	2 years	FAN BEARING TYPE Rifle Bearing FAN SPEED 650-1800 RPM ± 10% FAN AIRFLOW 62 CFM ± 10% FAN AIR PRESSURE 2.5 mmH2O ± 10% FAN NOISE LEVEL 8 - 27 dBA

Sickleflow X (Blue)	R4-SXDP-20FB-A1	NA	Rp	75.000	120 x 120 x 15 mm	50,000 hrs	1 Year	Fan Speed : 2,000 RPM
Sickleflow X (Red)	R4-SXDP-20FR-A1	NA	Rp	75.000				
Sickleflow X (Green)	R4-SXDP-20FG-A1	NA	Rp	75.000				
Accessories								
ARGB LED STRIP	MFX-GSHN-40NNN-R1	R	Rp	177.000	White, Rubber	400mm / 15.7 inch	2 Years	Addressable Gen 2 LED Soft Rubber Double Sides Adhesive
MINI ADDRESSABLE RGB LED CONTROLLER	MFW-ACHN-NNNNN-R1	R	Rp	141.000	44 x 25 x 15 mm		2 Years	LED CONNECTOR 4 Port POWER CONNECTOR SATA RATED CURRENT 2A SOFTWARE No ACCESSORY 1 set of 1 to 4 ARGB Cable and Sata cable
1-5 ARGB Splitter	MFX-AWHN-1NNN5-R1	R	Rp	97.000	58cm			PROFILE Addressable RGB LENGTH 58cm / 22.83 inch CONNECTOR 3-Pin RATED VOLTAGE 5V
1-3 ARGB Splitter	MFX-AWHN-3NNN1-R1	NA	Rp	95.000	50cm (19.68 inch)			ADDRESSABLE RGB 1-TO-3 SPLITTER CABLE Allow users to extend multiple addressable RGB LED fans to build up aesthetically beautiful lighting systems. With the length of 50 cm, you can get the lighting you want without any hassles.
CMT ACC ARGB & PWM HUB 1 - 6 Port	MFX-ZHHN-1NNN6-R1	R	Rp	195.000	103 x 65 x 16 mm			6 Ports x 4 Pin PWM, FAN RATED VOLTAGE, 12VDC, FAN SAFETY CURRENT, 2.0 A (1 Port) / Total 4.5 A (6 Ports), RGB CONNECTOR, 6 Ports x 3 Pin Addressable RGB RGB RATED VOLTAGE, 5V DC, RGB SAFETY CURRENT, 2.0 A (1 Port) / Total 4.5 A (6 Ports) POWER CONNECTOR, SATA, POWER SAFETY CURRENT, 4.5 A (Max) WEIGHT, 62g, WARRANTY, 2 years, SERIES, MasterFan, RGB Accessories COOLER TYPE, RGB Accessories, NOTE, Size of the ARGB devices that you are connecting should be within 12*6mm
Masterfan Pro RGB Controller	MFY-RCSN-NNUDK-R1	R	Rp	349.000			2 years	Dimension 90mm x 53mm x 14mm, Material : Plastic, PCB, Control Method: Cooler Master Software, Input Connector : SATA Power, Output Channel Voltage : 12V
RGB Splitter Cable	R4-ACCY-RGBS-R2	R	Rp	86.000			2 years	Cable Material PVC Pin Contact Material rass Color Black Total Length 58 cm Connector Type 4-pin (12V,G,R,B) Connector ithstanding Voltage 300 V (min) Pin Rated Current 3A
Small A-RGB Controller	MFX-ACBN-NNUNN-R1	R	Rp	262.000	59.5 x 23.5 x 15mm (2.3 x 0.9 x 0.6")		2 years	LED Connector 1 Port, Interface Micro USB 2.0' Power Connector SATA Power Software Yes' Accessory 1 x SATA & Thermal Detection Cable 1 x 1 to 3 ARGB Cable & Cable to sync MB' 1 x Y Cable
Wired RGB Controller C10L	RE-C10L-RGB-R1	NA	Rp	59.000			2 years	Dimension 45 x 16 x 8mm Material Plastic, PCB Connector 4-Pin Output Channel Voltage 12V Rated Current 2A Included Accessories 1 * Extension Cable

THERMAL INTERFACE

Product	Part No.	Stock	MSRP	Thermal Conductivity	Volume	Color	Remark
Cryofuze	MGZ-NDSG-N07M-R2	R	Rp 167.000	14 (W/m-K)	2gr	Grey	High Insulation. High Temperature Resistance. Toxic Free. Low Volatility
ICE FUSION V2	RG-ICF-CWR3-GP	R	Rp 128.000	5 (W/m-K)	40g	Grey	
CMT PST MasterGel Pro V2	MGY-ZOSG-N15M-R3	R	Rp 99.000	9 (W/m-K)	1.5ml	Grey	
CMT PST MasterGel Maker New	MGZ-NDSG-N15M-R2	R	Rp 163.000	11 (W/m-K)	1.5ml	Grey	
CMT PST MasterGel Pro New	MGY-ZOSG-N15M-R2	NA	Rp 99.000	8 (W/m-K)	1.5ml	Grey	
CMT PST MasterGel Regular New	MGX-ZOSG-N15M-R2	R	Rp 68.000	5 (W/m-K)	1.5ml	Grey	
RPD Grease High Performance	HTK-002-U1	R	Rp 45.000	0.8 watts/meter-C	4.6g	White	Suitable for CPU, chipsets on Mainboard, VGA card, etc. Easy to use Zif Socket Templates ensure correct applying area with various CPU socket types. Produces an even layer when using applicator. Dielectric. Wide range of application temperature

THERMAL PAD

Product	Part No.	Stock	MSRP	Thermal Conductivity	Dimension	Color	Remark
Thermal Pad Pro 1.0mm	TPY-NDPB-9010-R1	R	Rp 167.000	15,3 (W/m-K)	95 x 45 mm	Blue	Formulated with Nano Particles Non-toxic and Non-corrosive Double-sided Adhesive Versatile and Easy Application
Thermal Pad Pro 2.0mm	TPY-NDPB-9020-R1	R	Rp 276.000	15,3 (W/m-K)	95 x 45 mm	Blue	
Thermal pad 0.5mm	TPX-NOPP-9005-R1	R	Rp 97.000	13,3 (W/m-K)	95 x 45 mm	Purple	
Thermal pad 1.0mm	TPX-NOPP-9010-R1	NA	Rp 118.000	13,3 (W/m-K)	95 x 45 mm	Purple	
Thermal Pad 1.5mm	TPX-NOPP-9015-R1	R	Rp 130.000	13,3 (W/m-K)	95 x 45 mm	Purple	
Thermal pad 2.0mm	TPX-NOPP-9020-R1	NA	Rp 141.000	13,3 (W/m-K)	95 x 45 mm	Purple	
Thermal pad 3.0mm	TPX-NOPP-9030-R1	NA	Rp 174.000	13,3 (W/m-K)	95 x 45 mm	Purple	

LED Tube

Product	Part No.	Stock	MSRP	Quantity	Diameter	Color	Remark
LED Tube Slv A1-12mm	MFX-ATHN-12NNN-R1	L	Rp 635.000	2 pcs (Panjang : 330mm / 13 inch)	12mm	White	Soft Rubber
LED Tube Slv A1-10mm	MFX-ATHN-10NNN-R1	L	Rp 587.000	2 pcs (Panjang 330mm / 13 inch)	10mm	White	Versatile Sizing

NOTEBOOK COOLING PAD									
Product	Part No.	Stock	MSRP	Color	Material	Dimension	Compatibility	Warranty	Remark
Connect Stand	MNX-SSRK-12NFK-R1	R	Rp 299.000	Black	Metal Mesh, Plastic, Rubber	295 x 170 x 74 mm	Multi Function	2 Years	FAN DIMENSIONS (L X W X H) 120 x 120 x 25 mm / 4.7 x 4.7 x 1 inch FAN SPEED 1200 RPM ± 10% FAN AIRFLOW 39.7 CFM ± 10% FAN NOISE LEVEL 22.3 dBA POWER USB 5V DC USB USB 2.0 x 1 CURRENT CONSUMPTION 0.21A
Notepal X150R	MNX-SWXB-10FN-R1	R	Rp 460.000	Black	Metal Mesh, Plastic, Rubber	386 x 280 x 58 mm	Supports up to 17" laptops	2 Years	FAN SPEED 1000 ±15% RPM FAN AIRFLOW 57 CFM FAN NOISE LEVEL 26 dBA POWER USB 5V DC USB 2.0 x 3, Type-C x 1
MasterNotepal Maker	MNZ-SMTE-20FY-R1	NA	Rp 793.000	Silver, Black LEDs	Aluminum, plastic, metal mesh	384.6 x 270 x 59.6 mm	Up to 17" Laptops / Tablets.	1 Year	Fan speed : 2000 RPM ± 10%. USB : 3.0 x 1, 2.0 x 3, 2.0 x 1 (Output), 3.0 Micro b x 1 (Power & Data Transmission), 2.0 Micro b x 1 (external power)
Notepal SF19	R9-NBC-SF93K-GP	NA	Rp 1.690.000	black	einforced Anti-slip Rubber / ABS Plastic	489.6 x 351.5 x 74.1 mm	Up to 19" laptops		Power Connector DC 5V / 4A adapter, Special Features Dual 135mm fans 4 Port USB 3.0 Hub, Fan Dimensions 135 x 135 x 25 mm / 5.3 x 5.3 x 1 inch Fan Speed 600 - 1300 RPM ± 15%, Fan Bearing Type Loop Dynamic Bearing (LDB) Fan Life Expectancy 160,000 Hours
Notepal SF17	R9-NBC-SF7K-GP	R	Rp 765.000	Black, Red LEDs	Mesh, Plastic, Rubber	180 x 180 x 15 mm	Up to 17" Laptops.		Fan speed : 700 - 1200 RPM ± 15%. USB : 4 Port USB 2.0 Hub.
Notepal X3	R9-NBC-NPX3-GP	R	Rp 391.000	Black	Plastics, Metal mesh, Rubber	400 x 310 x 51~71 mm	Support ups to 17" laptops.		Fan speed : 500 ~ 850(±15%) R.P.M. USB : USB 2.0/1.1 x1, Mini-USB x1 (For power input)
Notepal U150R	R9-U150R-16FK-R1	R	Rp 620.000	Black	Metal Mesh, Plastic	350 x 250 x 23~39mm	Support up to 15.4" laptops		Fan Dimension 140 x 140 x 15mm (W / H / D) Fan Speed 1200 rpm+/-15% Fan Speed Adjustment Single speed Fan Airflow 38 CFM Fan Noise Level 21 dB(A) Power USB (DC 5V) USB 2.0/1.1 x1
Notepal U3 PLUS w/ 3 fans (Black)	R9-NBC-U3PK-GP	R	Rp 443.000	Black	Aluminum, Plastic, Rubber	435 x 333 x 76 mm	Supports up to 19" laptops		Fan speed : 950 - 1800 ±15% RPM. USB : USB 2.0/1.1 x1 (Extension)
Notepal U3 PLUS w/ 3 fans (Silver)	R9-NBC-U3PS-GP	L	Rp 443.000	Silver					
Notepal U2 Plus V2	MNX-SWUK-20FNN-R1	R	Rp 381.000	Black	Aluminum, Metalmesh, Plastic, Rubber, Cloth	343 x 266 x 53 mm	Supports up to 17" laptops		FAN SPEED 2000 RPM ± 10% FAN AIRFLOW 31 CFM FAN NOISE LEVEL 21 dBA POWER USB 5V DC USB 2.0/1.1 x 1 (For Power Input) CURRENT CONSUMPTION 0.36A POWER CONSUMPTION 1.8W
Notepal U2 PLUS w/ 2 fans (Black)	R9-NBC-U2PK-GP	R	Rp 356.000	Black	Aluminum, metal mesh, plastic, rubber.	346 x 282 x 60 mm	Supports up to 17" laptops		Fan speed : 2000 ± 10% RPM. USB : USB 2.0/1.1 x 1 (for power input).
Notepal U2 PLUS w/ 2 fans (Silver)	R9-NBC-U2PS-GP	R	Rp 356.000	Silver					
Notepal i100 Black	R9-NBC-I1HK-GP	R	Rp 190.000	Black	Metal Mesh, Plastic	350 x 250 x 23~39 mm	Support up to 15.4" laptops		Fan speed : 1200 rpm+/-15%. USB : USB 2.0/1.1 x1.
CMT NPL A200	R9-NBC-A2HK-GP	NA	Rp 446.000		Aluminum, metal mesh, plastic, rubber.	367 x 262 x 24.5~60 mm	Supports up to 16" laptops		140 x 140 x 15 mm / 5.5 x 5.5 x 0.6 inch, FAN SPEED, 700-1200 RPM ± 15% FAN SPEED ADJUSTMENT, Yes, FAN AIRFLOW, 92 CFM, FAN NOISE LEVEL 20 - 28 dBA, POWER, USB 5V DC, USB, USB 2.0/1.1 x 2, Mini USB x 1 COMPATIBILITY, Supports up to 16" laptops, COOLER TYPE, Notebook Cooler SERIES, Notepal
NOTEPAL X-LITE II	R9-NBC-XL2K-GP	R	Rp 246.000		Metal + plastic	330 x 251.2 x 28.2mm	Supports up to 15.6" laptops		Fan Speed 700 – 1400 ± 150 RPM / 1100 ± 150 RPM (w/o hub), Fan Airflow 46.8 CFM / 38 CFM (w/o hub), Fan Noise Level 15 – 21 dBA, Power USB 5V DC USB, Mini USB x1 + USB2.0 x2 (USB hub version), USB 2.0/1.1 x1 (w/o hub version), Current Consumption 0.20 - 0.34A / 0.25A (w/o hub), Power Consumption 0.9W - 1.7W / 1.25W (w/o hub)
Notepal X-Slim II	R9-NBC-XSLI-GP R9-NBC-XS2K-GP R9-NBC-XS2K-GP	R	Rp 194.000		Metal, mesh, rubber	350 x 249 x 44 mm	Supports up to 15.6" laptops		Fan speed : 900 ± 15% RPM. USB : USB 2.0x1.
Notepal L1	R9-NBC-NPL1-GP	R	Rp 206.000		Plastic, Metal Mesh, Rubber	390 x 310 x 20~47 mm	Support all 17" and smaller laptops	Fan speed : 1400 ±15% R.P.M.	
NOTEPAL L2	MNW-SWTS-14FN-R1	R	Rp 256.000		Full Mesh Metal Design	379 x 285 x 47.5 mm	Support up to 17" laptop	Fan Dimension Ø160x15 mm, Fan Speed 1400 ± 15% RPM, Fan Air Flow 6 ~ 20 CFM (Max) Fan Noise 29 dBA (Max), Power USB 5V DC, Ports USB 2.0 x 1, Micro USB x 1 Current Consumption 0.45 A, Power Consumption 2.25 W	
Notepal Ergostand Air (Black)	MNX-SSEK-NNNNN-R1	R	Rp 450.000		Aluminum, Rubber	298 x 215 x 17mm	Supports up to 15" laptops	Aluminum Alloy Top Grade Finish and Design Soft Rubber Padding Ergonomic Versatility	
Notepal Ergostand Air (Silver)	MNX-SSEW-NNNNN-R1	R	Rp 450.000		Aluminum, Rubber	298 x 215 x 17mm	Supports up to 15" laptops	Aluminum Alloy Top Grade Finish and Design Soft Rubber Padding Ergonomic Versatility	

Notepal CMC3	R9-NBC-CMC3-GP	R	Rp	134.000		Plastic, rubber	322 x 290 x 50 mm	Supports up to 15" laptops	<p>Fan Speed 700 R.P.M. ±15%, Fan Speed Adjustment Single fan speed Fan Airflow 74.5 CFM, Fan Noise Level 21 dBA</p> <p>Fan speed : 1200 ± 15%RPM USB : USB2.0 x 1</p> <p>Fan speed : 1400(±15%) R.P.M. USB : USB 2.0/1.1 x1, (For Power Input)</p> <p>Fan Dimension 140 x 140 x 15 mm Fan Speed 700~1400 ± 200 RPM Fan Air Flow 46.8 CFM Fan Air Pressure 1.24 mmH2O Fan Noise 29 dBA Power USB 5V DC USB 2.0 x 4, Mini x 1, Micro x 1 Current Consumption 0.20 A Power Consumption 1.0 W</p> <p>1 Year</p> <p>Weight 1.12kg (39.51oz) Dimensions 340 x 290.2 x 46.18 – 211.5mm (13.3 x 11.4 x 1.8 – 8.33 inch) Fan Dimensions 160 x 15mm (6.3 x 0.59 inch) Fan Speed 700 – 1400 ± 150RPM Fan Airflow 35 – 70 CFM Fan Noise Level 16 - 21 dBA Power USB 5V DC USB Mini USB x1 + USB2.0 x2 + VR Current Consumption 0.22 - 0.38A Power Consumption 1.1W - 1.9W</p>
NOTEPAL COMFORTER AIR BLACK	R9-NBC-CAAK-GP	C	Rp	375.000		Plastic, Sponge with clothing	380 x 276.2 x 46.5mm	Supports up to 15.6" laptops and all sizes of tablets	
NOTEPAL L200	R9-NBC-I2HK-GP	NA	Rp	246.000	Black	Mesh + Plastic	342 x 262 x 33.43 mm	Supports up to 15.6" laptops	
Notepal Ergostand IV	R9-NBS-E42K-GP	R	Rp	543.000	Black	Metal Mesh, Plastic, Rubber	370 x 265 x 40 mm	Support up to 17" laptop	
Notepal Ergostand Lite	R9-NBS-ESLK-GP	R	Rp	381.000	Black	Mesh + plastic	340 x 290.2 x 46.18 x 211.5mm	Supports up to 15.6" laptops	

Effective Date: 03 Januari 2022

GAMING KEYBOARD MASTERKEY SERIES									
Product	Part No.	Stock	MSRP	Dimension	RGB	Key Switch Types	Interface	Warranty	Remark
CK530 V2 Blue Swtch	CK-530-GKTL1-US	L	Rp 881.000	380 x 135 x 40 mm	Yes	Mechanical Switch Blue	USB 2.0	2 years	The CK530 V2 Gaming Mechanical Keyboard gets the job done at homebase or to-go with Mechanical switches and On-the-Fly Controls in a portable, tenkeyless format.
CK530 V2 Brown switch	CK-530-GKTM1-US	L	Rp 881.000	380 x 135 x 40 mm	Yes	Mechanical Switch Brown	USB 2.0	2 years	
CK530 V2 Red switch	CMGMNGKEYBCK00006	L	Rp 881.000	380 x 135 x 40 mm	Yes	Mechanical Switch Red	USB 2.0	2 years	
SK620 Black Brown Swch	SK-620-GKTM1-US	L	Rp 979.000	Standard: 293 x 103 x 30.28 mm, Feet Open: 293 X 103 X 43.03 mm	Yes	Low Profile Mechanical Switch Brown	USB Type-C (Keyboard Side), USB 2.0 Type A (Computer Side)	2 years	Portabel 60% Compact Layout Low Profile RGB Mechanical Switches Keycaps Ergonomis Desain Plat bagian atas yang ramping Desain Brushed Aluminum Pencahayaan RGB & RGB Lightbar On-the-fly Adjustment - Lighting & Macros Dudukan Keyboard 32-bit ARM Cortex CPU Tombol pengatur OS pada Keyboard macOS, iOS, Android & Windows
SK620 White Brown Swch	SK-620-SKTM1-US	R	Rp 979.000	Standard: 293 x 103 x 30.28 mm, Feet Open: 293 X 103 X 43.03 mm	Yes	Low Profile Mechanical Switch Brown	USB Type-C (Keyboard Side), USB 2.0 Type A (Computer Side)	2 years	
SK620 White Blue Switch	SK-620-SKTL1-US	R	Rp 979.000	Standard: 293 x 103 x 30.28 mm, Feet Open: 293 X 103 X 43.03 mm	Yes	Low Profile Mechanical Switch Blue	USB Type-C (Keyboard Side), USB 2.0 Type A (Computer Side)	2 years	
SK620 Black Blue	SK-620-GKTL1-US	R	Rp 979.000	Standard: 293 x 103 x 30.28 mm, Feet Open: 293 X 103 X 43.03 mm	Yes	Blue Low Profile	USB Type-C (Keyboard Side), USB 2.0 Type A (Computer Side)	2 Years	The Cooler Master SK620 is the wired version of SK622, taking a modern approach to the classic mechanical keyboard with low profile switches housed in a sleek chassis for a drool-worthy aesthetic. The 60% keyboard layout is outfitted with low profile mechanical RGB switches with upgraded ergonomic keycaps from the previous version for a typing experience that feels as good as the keyboard looks. The keyboard supports both Mac and Windows devices, and you have the ultimate on-the-go keyboard for both work and play.
SK620 Black Red	SK-620-GKTR1-US	R	Rp 979.000	Standard: 293 x 103 x 30.28 mm, Feet Open: 293 X 103 X 43.03 mm	Yes	Red Low Profile	USB Type-C (Keyboard Side), USB 2.0 Type A (Computer Side)	2 Years	
SK620 White Red	SK-620-SKTR1-US	R	Rp 979.000	Standard: 293 x 103 x 30.28 mm, Feet Open: 293 X 103 X 43.03 mm	Yes	Red Low Profile	USB Type-C (Keyboard Side), USB 2.0 Type A (Computer Side)	2 Years	
CK350 Outemu Brown	CK-350-KKOM1	R	Rp 783.000	440 x 1400 x 45 mm	Yes	Outemu Brown	USB 2.0	2 Years	
CK350 Outemu Red	CK-350-KKOR1	L	Rp 783.000	440 x 1400 x 45 mm	Yes	Outemu Red	USB 2.0	2 Years	ON-THE-FLY CONTROLS, STANDARD LAYOUT, RGB BACKLIGHTING, MECHANICAL SWITCHES,
CK350 Outemu Blue	CK-350-KKOL1-US	C	Rp 783.000	440 x 1400 x 45 mm	Yes	Outemu Blue	USB 2.0	2 Years	
MasterKeys MK120 US	MK-120-KKMF1-US	C	Rp 730.000	118 (L) x 78.5 (W) x 39.5 (H) mm	Yes	Brown	USB 2.0		Switch Type Mem-chnical Clicky, Switch Lifespan 50M+, Material Plastic Color Black, LED Color RGB Lighting Mode Per-key full backlight, multiple modes and reactive effects. Controllable through FN key combo. FW Updates Yes, online updates for LED modes, Polling Rate 125 Hz On board Memory 32KB, Multimedia Through FN, Connector Cable USB 1.1

GAMING HEADSET									
Product	Part No.	Stock	MSRP	Frequency Response	Impedance	Connector	Microphone	Warranty	Remark
MH670	MH-670	R	Rp 1.460.000	5-25,000Hz / 3.5mm mode, 20-20,000Hz / 2.4G mode	32Ω	N/A	Detachable flexible microphone	2 Years	The MH670 Gaming Headset is a sleek, comfortable wireless headset that provides maximum sound quality and superior versatility with minimal hassle. Latency-free 2.4GHz wireless connectivity, high-quality audio, and near-universal connectivity combine to give you a supremely convenient gaming headset that gives you your audio the way you want it.
MasterPulse MH752	MH-752	R	Rp 1.198.000	20-20,000Hz	26Ω	3.5mm 4-pole jack / USB Type A	Detachable flexible microphone	2 Years	The MH752 Gaming Headset features premium quality sound with unprecedented comfort, ideal for those long battle royales. 40mm Neodymium drivers with virtual 7.1 surround sound offer the situational awareness needed to hear footsteps and chests, while plush, lightweight ear cups provide a fit so comfortable, your pillow feels like bricks in comparison.
MasterPulse MH751	MH-751	R	Rp 1.011.000	20-20,000Hz	26Ω	3.5mm 4-pole jack	Detachable flexible microphone	2 Years	The MH751 Gaming Headset offers high-quality sound with high-comfort fit for your longest battle royale sessions. 40mm Neodymium drivers provide full, balanced sound, while the omnidirectional mic keeps communications crystal clear within your squad. And plush, swiveling earcups provide superior comfort as you pursue a victory royale.
MasterPulse MH710	MH-710	NA	Rp 573.000	20 Hz - 20,000 Hz	16 Ω	3.5mm 4-pole jack	Omni-Directional	2 years	
MasterPulse MH703	MH-703	NA	Rp 489.000	20 Hz - 20,000 Hz	17 Ω	3.5mm 4-pole jack	Omni-Directional		
CMT HST MH650	MH650	NA	Rp 920.000	20Hz -20,000Hz	32Ω	3.5mm 4-pole jack	Omni-Directional	2 Years	EXPERIENCE IMMERSIVE GAMING The MH650 Gaming Headset provides an immersive experience in a portable package ideal for console and PC gamers. Virtual 7.1 surround sound and omnidirectional boom mic offer high-quality sound and comms, wrapped in a sleek matte black design and fully customizable RGB illumination - and cushioned ear cups provide the perfect fit for those marathon sessions.
CMT HST MH630	MH630	NA	Rp 711.000	50Hz - 18,000Hz	32Ω	3.5mm Gold Plated	Omni-Directional	2 Years	CLEAR COMMS, CRYSTAL CLARITY Simple yet powerful, the MH630 Gaming Headset gives you all the features you need to be a leader on the battlefield. Rich, booming sound, crystal-clear comms, and multi-platform connectivity give you universal quality across the board. Fully featured and without any weaknesses, this strong contender gives you a clear aural advantage over the rest of the competition.
CH-321	CH321	C	Rp 430.000	20-20,000Hz	16Ω	2.3m Type A USB cable	Omni-Directional		
GAMING MOUSE									
Product	Part No.	Stock	MSRP	Color	Body Coating Material	DPI	Connector	Warranty	Remark
MM731 Black Matte	MM-731-KKOH1	R	Rp 980.000	Black Matte	ABS PLASTIC, RUBBER, PTFE	400-800-1200(DEFAULT)-1600-3200-8000-19000	WIRED, 2.4 GHZ, BLUETOOTH 5.1	2 Year	
MM730 Black Matte	MM-730-KKOL1	R	Rp 791.000	Black Matte	ABS Plastic, Rubber, PTFE	400-800-1,200(Default)-1600-3200-6400-16000	Wired USB		
MM730 White Matte	MM-730-WWOL1	R	Rp 791.000	White Matte	ABS Plastic, Rubber, PTFE	400-800-1,200(Default)-1600-3200-6400-16000	Wired USB		
MM720 Matte Black	MM-720-KKOL1	NA	Rp 659.000	Black Mate	ABS, PTFE	7 Levels (400, 800, 1200 (default), 1600, 3200, 6400, 16000)	USB 2.0		
MM711 Glossy White	MM-711-WWOL2	R	Rp 627.000	Glossy White	ABS Plastic	7 Levels (400, 800, 1200 (default), 1600, 3200, 6400, 16000)	USB 2.0		
MM711 Matte Black	MM-711-KKOL1	R	Rp 627.000	Matte Black	ABS Plastic	7 Levels (400, 800, 1200 (default), 1600, 3200, 6400, 16000)	USB 2.0		
MM711 Golden Red	MM-711-GROL1	R	Rp 627.000	Golden Red	ABS Plastic	7 Levels (400, 800, 1200 (default), 1600, 3200, 6400, 16000)	USB 2.0		
MM711 Metallic Blue	MM-711-MBOL1	R	Rp 627.000	Metallic Blue	ABS Plastic	7 Levels (400, 800, 1200 (default), 1600, 3200, 6400, 16000)	USB 2.0		
CM110	CM-110-KKWO1	R	Rp 344.000	Black	ABS Plastic, Rubber	5 Levels (400, 800, 1600, 3200, 6000)	USB 2.0		
MasterMouse 710 (Black Mate)	MM-710-KKOL1	NA	Rp 627.000	Black Mate	ABS Plastic	Up to 16000	USB 2.0		
CM310	CM-310-KKWO2	R	Rp 399.000	Black	ABS Plastic / Rubber	Up to 10000	USB 2.0		

GAMING MOUSE PAD

Product	Part No.	Stock	MSRP	Surface Type	Base	Dimension	Warranty
Mousepad MP511 XXL Size	MP-511-CBXC1	R	Rp 685.000	CORDURA® Fabric, Gaming-optimized texture	100% Natural Rubber	1220 x 610 x 3 mm ± 5mm	No Warranty
Mousepad MP511 XL Size	MP-511-CBEC1	R	Rp 465.000	CORDURA® Fabric, Gaming-optimized texture		900 x 400 x 3 mm ± 5mm	
Mousepad MP511 L Size	MP-511-CBLC1	R	Rp 389.000	CORDURA® Fabric, Gaming-optimized texture		450 x 400 x 3 mm ± 5mm	
HS-M Weapon of choice M4 SSK	SGS-6010-KHM-1-G	L	Rp 290.000	SKK Surface TM		350 x 260 x 4 mm	
CS-M Weapon of Choice M4 DM	SGS-4000-WSM-1-G	L	Rp 268.000	Duramesh TM		405 x 285 x3 mm	
MasterAccessory MP510-S	MPA-MP510-S	NA	Rp 149.000	Cordura fabric - surface Rubber - base	Black	250x210x3mm	DURABLE, CORDURA® FABRIC ANTI-FRAY, STITCHING GLOW-IN-THE-DARK LOGO SPASH-PROOF SURFACE
MasterAccessory MP510-M	MPA-MP510-M	NA	Rp 199.000	Cordura fabric - surface Rubber - base	Black	320x270x3mm	
MasterAccessory MP510 L	MPA-MP510-L	NA	Rp 280.000	Gaming-optimized texture with Microscopic Mesh	100% Natural Rubber	450x350x3mm	No Warranty
MasterAccessory MP510 XL	MPA-MP510-XL	NA	Rp 399.000			900x400x3mm	
MasterAccessory MP860	MPA-MP860-OSA-N1	L	Rp 1.120.000			Dual Side (Cloth side, smooth aluminium side)	
Wrist Rest							
MasterAccessory WR531 TKL	WR-531-CRT*1	R	Rp 133.000	Jersey Cloth, PU Foam, Styrene- butadiene Rubber	Black	380 x 95 x 15mm ± 5mm	1 Year Warranty
MasterAccessory WR531 Full Size	WR-531-CRF*1	R	Rp 145.000	Jersey Cloth, PU Foam, Styrene- butadiene Rubber	Black	460 x 95 x 15mm ± 5mm	
Earmuff							
Product	Part No.	Stock	MSRP	Deskripsi			
MH751/752 Earmuff	622015150-GP, 622015160-GP	R	Rp 210.000	Earmuff replacement for MH751/752			
MH630 Earmuff	622029700-GP, 622029710-GP	L	Rp 210.000	Earmuff replacement for MH630			
MH650 Earmuff	622029760-GP, 622029770-GP	L	Rp 210.000	Earmuff replacement for MH650			
MH670 Earmuff	622029810-GP, 622029820-GP	L	Rp 210.000	Earmuff replacement for MH670			